

TOP VIEW







	Specifications		Notes		Revision History						
Description	Value	e Unit Notes		otes	Version	Description			Date	Approved	
Shape	Round		1) All dimensions are in mm unless otherwise noted		1	Released from Engineering			2/5/2014	J.S.	
Resonant Frequency	400	(Hz)	2) All parts meet RoHS								
Frequency Range	400 ~ 4,000	(Hz)	7								
SPL @ 10cm	85	(dBA)									
Impedance	8	(Ohm)									
Cone Material	Paper										
Nominal Power	0.5	(W)									
Max Power	1	(W)									
Mount Type	Flush Mount				Drawn by	Date	Checked by	Date	Approved by	Date	
Operating Temperature	-25 ~ +55	°C			G.W.	1/27/2014	C.E.	1/28/2014	J.S.	2/5/2014	
Storage Temperature	-25 ~ +55	°C		Dynamia Spaakar	peaker SP570408-2						
Weight	42	(g)		Dynamic Speaker	Dynamic Speaker		373/0408-2				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Speakers & Transducers category:

Click to view products by DB Unlimited manufacturer:

Other Similar products are found below:

FC-30814-P127 AS02832MR-2-R PB-1220PE PB-2015PQ 900-00001 AB2025B-LW50-R SWFK-31736-000 PT-2065FW PT-4175W AT-2830-TW-LW35-R ED-30761-000 CI-30120-A42 SMT-0440-T-2-R PB-0927PQ BF-7083-000 CTX323B220 SMS2020-08H4.5 LF

BDT1717-08H6.5W56MLF GSPK1003PN-8R0.2W-L100 GSPK151103TN-8R0.2W GSPK2014035PN-8R0.5W-L100 AS03608MR-LW100-R 24520 SMT-0540-S-2-R 1450069 9091653 9091661 IPS-G6000-5 9090231 FS50MS0820-H9.7 FS4014-4-2W PBM4-13.B29R.A115.0663 PBM4-13.B31R.A115.0663 PBM4-13.B33R.A115.0663 PBM4-13.B35R.A115.0663 A-10-6-BG360-HD1Z-GA-M4Z-ZW A-10-6-BG410-HD1Z-AA-AGZ-ZW A-10-6-BG410-HD1Z-AA-M4Z-ZW A-10-6-BG310-HD1Z-AA-AGZ-ZW A-10-6-BG310-HD1Z-AA-M4Z-ZW A-10-6-BG310-HD1Z-GA-M4Z-ZW A-10-6-BG340-HD1Z-AA-M4Z-ZW A-10-6-BG340-HD1Z-AA-AGZ-ZW A-10-6-BG340-HD1Z-AA-M4Z-ZW A-10-6-BG340-HD1Z-AA-M4