TOP VIEW	V S	IDE VIE	EW (1)	SIDE VIEW (	2)		BOTT	om VI	EW	
12.8±0.3	0.0 					3-R0.7 3±0.3	2±0.3			0.1 C:D±8:51
Sp	ecifications				1		Revisio	on History		
Sp Description	ecifications Value	Unit		Notes	Version		Revisio	-	Date	Approved
			1) All dimensions are in mm		Version 1			-	<b>Date</b> 10/21/2013	Approved J.S
Description	Value				-		Description	-		
Description Technology	Value Electro-Mechanical		1) All dimensions are in mm		-		Description	-		
<b>Description</b> Technology Resonant Frequency	Value Electro-Mechanical 2,400	(Hz)	1) All dimensions are in mm		-		Description	-		
Description Technology Resonant Frequency Rated Voltage	Value Electro-Mechanical 2,400 1.5	(Hz) (V)	1) All dimensions are in mm		-		Description	-		
<b>Description</b> Technology Resonant Frequency Rated Voltage SPL @ 10cm	Value Electro-Mechanical 2,400 1.5 80	(Hz) (V) (dBA)	1) All dimensions are in mm		-		Description	-		
Description Technology Resonant Frequency Rated Voltage SPL @ 10cm Coil Resistance	Value           Electro-Mechanical           2,400           1.5           80           15	(Hz) (V) (dBA)	1) All dimensions are in mm		-		Description	-		
Description Technology Resonant Frequency Rated Voltage SPL @ 10cm Coil Resistance Mount Type	Value Electro-Mechanical 2,400 1.5 80 15 Surface Mount	(Hz) (V) (dBA) (ohm)	1) All dimensions are in mm		-		Description	-		
Description Technology Resonant Frequency Rated Voltage SPL @ 10cm Coil Resistance Mount Type Voltage Range	Value           Electro-Mechanical           2,400           1.5           80           15           Surface Mount           1~3	(Hz) (V) (dBA) (ohm) (V)	1) All dimensions are in mm		-		Description	-		
Description Technology Resonant Frequency Rated Voltage SPL @ 10cm Coil Resistance Mount Type Voltage Range Max Rated Current	Value           Electro-Mechanical           2,400           1.5           80           15           Surface Mount           1~3           30	(Hz) (V) (dBA) (ohm) (V)	1) All dimensions are in mm			Release	Description ed from Engi	neering	10/21/2013	J.S
Description Technology Resonant Frequency Rated Voltage SPL @ 10cm Coil Resistance Mount Type Voltage Range Max Rated Current Housing Material	Value           Electro-Mechanical           2,400           1.5           80           15           Surface Mount           1~3           30           PPS	(Hz) (V) (dBA) (ohm) (V) (mA) °C °C	1) All dimensions are in mm		Drawn by A.B.	Release	Description ed from Engi Checked by C.E.	Date	10/21/2013	J.S

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Speakers & Transducers category:

Click to view products by DB Unlimited manufacturer:

Other Similar products are found below :

 FC-30814-P127
 AS02832MR-2-R
 PB-1220PE
 PB-2015PQ
 900-00001
 AB2025B-LW50-R
 SWFK-31736-000
 PT-2065FW
 PT-4175W
 AT 

 2830-TW-LW35-R
 ED-30761-000
 CI-30120-A42
 SMT-0440-T-2-R
 PB-0927PQ
 BF-7083-000
 CTX323B220
 SMS2020-08H4.5 LF

 BDT1717-08H6.5W56MLF
 GSPK1003PN-8R0.2W-L100
 GSPK151103TN-8R0.2W
 GSPK2014035PN-8R0.5W-L100
 AS03608MR-LW100 

 R
 24520
 SMT-0540-S-2-R
 1450069
 9091653
 9091661
 IPS-G6000-5
 9090231
 FS50MS0820-H9.7
 FS4014-4-2W
 PBM4 

 13.B29R.A115.0663
 PBM4-13.B31R.A115.0663
 PBM4-13.B33R.A115.0663
 PBM4-13.B35R.A115.0663
 A-10-6-BG360-HD1Z-GA-M4Z-ZW

 ZW
 A-10-6-BG410-HD1Z-AA-M4Z-ZW
 A-10-6-BG410-HD1Z-GA-M4Z-ZW
 A-10-6-BG310-HD1Z-AA-M4Z-ZW
 A-10-6-BG310-HD1Z-AA-M4Z-ZW

 A-AGZ-ZW
 A-10-6-BG310-HD1Z-AA-M4Z-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-M4Z-ZW
 A-10-6-BG340-HD1Z-AA-M4Z-ZW

 A-10-6-BG340-HD1Z-GA-M4Z-ZW
 A-10-6-BG360-GT1Z-AA-M4Z-ZW
 A-10-6-BG360-HD1Z-AA-AGZ-ZW
 A-10-6-BG360-HD1Z-AA-AGZ-ZW