

Specifications			Notes		Revision History					
Description	Value	Unit	Notes		Version	Description		Date	Approved	
Technology	Piezo		1) All dimensions are in mm	unless otherwise noted	1	Release	ed from Engi	neering	10/21/2013	J.S
Resonant Frequency	3,400	(Hz)	2) All parts meet RoHS							
Rated Voltage	9	(V)								
SPL @ 10cm	90	(dBA)								
Capacitance	25,000	(pF)								
Mount Type	Flush Mount									
Voltage Range	3 ~ 28	(V)								
Max Rated Current	5	(mA)								
Housing Material	ABS				Drawn by	Date	Checked by	Date	Approved by	Date
Operating Temperature	-20 ~ +60	°C			A.B.	10/21/2013	C.E.	10/21/2013	J.S	10/21/2013
Storage Temperature	-30 ~ +70	°C		Piezo Transducer	TP303409-1					
Weight	8	(g)	DB UNLIMITED			17505409-1				

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Speakers & Transducers category:

Click to view products by DB Unlimited manufacturer:

Other Similar products are found below :

 FC-30814-P127
 AS02832MR-2-R
 PB-1220PE
 PB-2015PQ
 900-00001
 AB2025B-LW50-R
 SWFK-31736-000
 PT-2065FW
 PT-4175W
 AT 

 2830-TW-LW35-R
 ED-30761-000
 CI-30120-A42
 SMT-0440-T-2-R
 PB-0927PQ
 BF-7083-000
 SMS2020-08H4.5 LF
 BDT1717 

 08H6.5W56MLF
 GSPK1003PN-8R0.2W-L100
 GSPK151103TN-8R0.2W
 GSPK2014035PN-8R0.5W-L100
 AS03608MR-LW100-R
 24520

 SMT-0540-S-2-R
 1450069
 9091653
 9091661
 IPS-G6000-5
 9090231
 FS50MS0820-H9.7
 FS4014-4-2W
 PBM4-13.B29R.A115.0663
 PBM4 

 13.B31R.A115.0663
 PBM4-13.B33R.A115.0663
 PBM4-13.B35R.A115.0663
 A-10-6-BG360-HD1Z-GA-M4Z-ZW
 A-10-6-BG410-HD1Z 

 AA-AGZ-ZW
 A-10-6-BG410-HD1Z-AA-M4Z-ZW
 A-10-6-BG310-HD1Z-GA-M4Z-ZW
 A-10-6 BG310-HD1Z-AA-AGZ-ZW
 A-10-6 

 BG310-HD1Z-AA-AGZ-ZW
 A-10-6-BG325-HD1Z-AA-M4Z-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW

 A-10-6-BG340-HD1Z-GA-M4Z-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW
 A-10-6-BG340-HD1Z-AA-AGZ-ZW