



SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 125V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 100MΩ Min
- 6、Withstanding Voltage: 500V AC/minute
- 7、Material: NY1066, UL94V-0

| Poles | Dimensions (mm) | |
|-------|-----------------|-------|
| | A | B |
| 2 | 1.25 | 4.25 |
| 3 | 2.50 | 5.50 |
| 4 | 3.75 | 6.75 |
| 5 | 5.00 | 8.00 |
| 6 | 6.25 | 9.25 |
| 7 | 7.50 | 10.50 |
| 8 | 8.75 | 11.75 |
| 9 | 10.00 | 13.00 |
| 10 | 11.25 | 14.25 |
| 11 | 12.50 | 15.50 |
| 12 | 13.75 | 16.75 |
| 13 | 15.00 | 18.00 |
| 14 | 16.25 | 19.25 |
| 15 | 17.50 | 20.50 |
| 16 | 18.75 | 21.75 |

| APPROVALS | | DATE | DRAWING NO. | |
|----------------|----------|---------------------|--------------------------------------|--------------|
| DRAWN | G.M.Chen | 2014/8/18 | A1251-XXP | |
| CHECKED | | | TITLE: 1.25mm Crimp Style Connectors | |
| APPROVALS | | | PART NO. A1251-XXP | |
| TOLERANCES ARE | | 30 ^{±0.15} | ±0.30 | ANGLE |
| | | 10 ^{±0.10} | ±0.20 | UNIT: mm |
| | | 5 ^{±0.10} | ±0.15 | SCALE: 1:1 |
| | | | | SHEET 1 OF 1 |
| ECN NO. | REV. | DATE. | DESCRIPTION. | PROJ. |
| | A | | NEW | |
| | | | | |



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [DEALON](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)
[803-43-024-10-001000](#)