



线数 Circuits	Dim.A	Dim.B	Dim.C
2	2.0	4.5	5.8
3	4.0	6.5	7.8
4	6.0	8.5	9.8
5	8.0	10.5	11.8
6	10.0	12.5	13.8
7	12.0	14.5	15.8
8	14.0	16.5	17.8
9	16.0	18.5	19.8
10	18.0	20.5	21.8
11	20.0	22.5	23.8
12	22.0	24.5	25.8

■ 技术参数

SPECIFICATIONS:

- ◆ 线数: 2~12
- ◆ Poles: 2~12
- ◆ 适用线规: AWG #30~#24
- ◆ Applicable Wire: AWG #30~#24
- ◆ 额定电压: 250V DC/AC
- ◆ Voltage Rating: 250V DC/AC
- ◆ 额定电流: 2.0A
- ◆ Current Rating: 2.0A
- ◆ 耐压: 800V AC
- ◆ Withstand Voltage: 800V AC
- ◆ 温度范围: -25°C~+85°C
- ◆ Working Temperature: -25°C~+85°C
- ◆ 绝缘电阻: ≥1000MΩ
- ◆ Insulation Resistance: 1000MΩ (MIN)
- ◆ 接触电阻: ≤20mΩ
- ◆ Contact Resistance: 20mΩ (MAX)
- ◆ 材质/颜色: 尼龙66 UL 94V-0 本色
- ◆ Material: Nylon 66 UL 94V-0 Color Nature

ECN NO.	REV.	DATE.	NEW	DESCRIPTION.	CHANGE.	CHECK.	APPRO.																																								
<p>APPROVALS</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th>DRAWN</th> <th>G.M.Chen</th> <th>DATE</th> <th>2015/7/17</th> </tr> <tr> <th>CHECKED</th> <td></td> <th>TITILE:</th> <td>2.0mm Crimp Style Connectors</td> </tr> <tr> <th>APPROVALS</th> <td></td> <th>PART NO.</th> <td>A2001-XXP</td> </tr> <tr> <th colspan="2">TOLERANCES ARE</th> <th>UNIT:</th> <td>mm</td> </tr> <tr> <td>30~40L ±</td> <td>±0.30</td> <th>ANGLE</th> <td>±2°</td> </tr> <tr> <td>10~30</td> <td>±0.20</td> <td></td> <td></td> </tr> <tr> <td>5~10</td> <td>±0.15</td> <th>SCALE:</th> <td>1:1</td> </tr> <tr> <td>~5</td> <td>±0.10</td> <th>DRAWING NO.</th> <td></td> </tr> <tr> <td></td> <td></td> <th>SHEET</th> <td>1 OF 1</td> </tr> <tr> <td></td> <td></td> <th>PROJ.</th> <td></td> </tr> </table>								DRAWN	G.M.Chen	DATE	2015/7/17	CHECKED		TITILE:	2.0mm Crimp Style Connectors	APPROVALS		PART NO.	A2001-XXP	TOLERANCES ARE		UNIT:	mm	30~40L ±	±0.30	ANGLE	±2°	10~30	±0.20			5~10	±0.15	SCALE:	1:1	~5	±0.10	DRAWING NO.				SHEET	1 OF 1			PROJ.	
DRAWN	G.M.Chen	DATE	2015/7/17																																												
CHECKED		TITILE:	2.0mm Crimp Style Connectors																																												
APPROVALS		PART NO.	A2001-XXP																																												
TOLERANCES ARE		UNIT:	mm																																												
30~40L ±	±0.30	ANGLE	±2°																																												
10~30	±0.20																																														
5~10	±0.15	SCALE:	1:1																																												
~5	±0.10	DRAWING NO.																																													
		SHEET	1 OF 1																																												
		PROJ.																																													



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [DEALON](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)  
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)  
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)  
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)  
[803-43-024-10-001000](#)