



■ 技术参数 SPECIFICATIONS:

- ◆ 线数: 4~40
- ◆ Poles: 4~40
- ◆ 适用线规: AWG #28~#22
- ◆ Applicable Wire: AWG #28~#22
- ◆ 额定电压: 250V DC/AC
- ◆ Voltage Rating: 250V DC/AC
- ◆ 额定电流: 3.0A
- ◆ Current Rating: 3.0A
- ◆ 耐压: 1000V AC
- ◆ Withstand Voltage: 1000V AC
- ◆ 温度范围: -25°C~+85°C
- ◆ Working Temperature: -25°C~+85°C
- ◆ 绝缘电阻: $\geq 1000M\Omega$
- ◆ Insulation Resistance: 1000MΩ (MIN)
- ◆ 接触电阻: $\leq 20m\Omega$
- ◆ Contact Resistance: 20mΩ (MAX)
- ◆ 材质/颜色: 尼龙 94V-0 本色
- ◆ Material: Nylon UL 94V-0 Color Nature
- ◆ 包装数量: 1000 pcs
- ◆ Packaging Quantity: 1000 pcs

线数 Circuits	尺寸			线数 Circuits	尺寸		
	Dim.A	Dim.B	Dim.C		Dim.A	Dim.B	Dim.C
4	2.0	4.5	6.0	20	18.0	20.5	22.0
6	4.0	6.5	8.0	22	20.0	22.5	24.0
8	6.0	8.5	10.0	24	22.0	24.5	26.0
10	8.0	10.5	12.0	26	24.0	26.5	28.0
12	10.0	12.5	14.0	28	26.0	28.5	30.0
14	12.0	14.5	16.0	30	28.0	30.5	32.0
16	14.0	16.5	18.0	—	—	—	—
18	16.0	18.5	20.0	40	38.0	40.5	42.0

APPROVALS		DATE	DRAWING NO.	
DRAWN	G.M.Chen	2015/7/17	ELECTRONICS CO.,LTD	
CHECKED			TITLE: 2.0mm Crimp Style Connectors	
APPROVALS			PART NO.	A2005-XXP
TOLERANCES ARE		30 ^{±0.15}	±2°	SHEET 1 OF 1
ECN NO.	REV.	DATE.	DESCRIPTION.	PROJ.
	A		NEW	



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [DEALON](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)
[803-43-024-10-001000](#)