



15	35.0	38.2	35.0
14	32.5	35.7	32.5
13	30.0	33.2	30.0
12	27.5	30.7	27.5
11	25.0	28.2	25.0
10	22.5	25.7	22.5
9	20.0	23.2	20.0
8	17.5	20.7	17.5
7	15.0	18.2	15.0
6	12.5	15.7	12.5
5	10.0	13.2	10.0
4	7.5	10.7	7.5
3	5.0	8.2	5.0
2	2.5	5.7	2.5
Circuits	Dim.A	Dim.B	Dim.C

- 技术参数 SPECIFICATIONS:
- ◆ 线数: 2~12
 - ◆ Poles: 2~12
 - ◆ 适用线规: AWG #28~#22
 - ◆ Applicable Wire: AWG #28~#22
 - ◆ 额定电压: 250V DC/AC
 - ◆ Voltage Rating: 250V DC/AC
 - ◆ 额定电流: 3.0A
 - ◆ Current Rating: 3.0A
 - ◆ 耐压: 1000V AC
 - ◆ Withstand Voltage: 1000V AC
 - ◆ 温度范围: -25°C ~ +85°C
 - ◆ Working Temperature: -25°C ~ +85°C
 - ◆ 绝缘电阻: ≥1000MΩ
 - ◆ Insulation Resistance: 1000MΩ (MIN)
 - ◆ 接触电阻: ≤10mΩ
 - ◆ Contact Resistance: 10mΩ (MAX)
 - ◆ 材质/颜色: 尼龙66 UL 94V-0 本色
 - ◆ Material: Nylon66 UL 94V-0 Color Nature
 - ◆ 包装数量: 1000 Pcs
 - ◆ Packaging Quantity: 1000 pcs

APPROVALS		DATE	TITLE:	
DRAWN	G.M.Chen	2015/7/17	EDELON 德之隆® ELECTRONICS CO.,LTD	
CHECKED			PART NO. A2501-XXP	
APPROVALS			2.54mm Crimp Style Connectors	
TOLERANCES ARE		ANGLE	UNIT:	SCALE:
30 ^{±0.15}	±0.30	±2°	mm	1:1
10 ^{±0.10}	±0.20			
5 ^{±0.10}	±0.15			
ECN NO.	REV.	DATE.	DESCRIPTION.	PROJ.
	A		NEW	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [DEALON](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)
[803-43-024-10-001000](#)