



技术参数:

线数 (Poles) : 2~12
 适用线规 (Applicable wires) : AWG22#~18#
 温度范围 (Temperature range) : -25°C~85°C
 额定电压 (Voltage rating) : 250V.Ac/Dc
 额定电流 (Current rating) : 7.5A
 接触电阻 (Contact resistance) : ≤0.02Ω
 绝缘电阻 (Insulation resistance) : ≥1000MΩ
 耐压 (Withstand voltage) : 1500V.Ac/1min
 材料 (Material) : (Nylon) 66 UL94V-2(0)
 孔座 (Housing)

Circuits	Dim.A	Dim.B
2	3.96	7.92
3	7.92	11.88
4	11.88	15.84
5	15.84	19.8
6	19.8	23.76
7	23.76	27.72
8	27.72	31.68
9	31.68	35.64
10	35.64	39.6
11	39.6	43.56
12	43.56	47.52

APPROVALS		DATE	PART NO.		SCALE	SHEET
DRAWN	G.M.Chen	2015/5/4	A3960-XXP		1:1	1 OF 1
CHECKED			A3960-XXP			
APPROVALS			A3960-XXP			
TITLE: 3.96mm Crimp Style Connectors ELECTRONICS CO.,LTD 德之隆®						
TOLERANCES ARE 30~40H± 40.30 ANGLE 10~30 40.20 5~10 40.15 ±2° DRAWING NO.						
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
	A		NEW			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [DEALON](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)
[803-43-024-10-001000](#)