



技术参数:

线数 (Poles) : 2~12  
 适用线规 (Applicable wires) : AWG22#~18#  
 温度范围 (Temperature range) : -25°C~85°C  
 额定电压 (Voltage rating) : 250V.Ac/Dc  
 额定电流 (Current rating) : 7.5A  
 接触电阻 (Contact resistance) : ≤0.02Ω  
 绝缘电阻 (Insulation resistance) : ≥1000MΩ  
 耐压 (Withstand voltage) : 1500V.Ac/1min  
 材料 (Material) : (Nylon) 66 UL94V-2(0)  
 孔座 (Housing)

Circuits	Dim.A	Dim.B
2	3.96	7.92
3	7.92	11.88
4	11.88	15.84
5	15.84	19.8
6	19.8	23.76
7	23.76	27.72
8	27.72	31.68
9	31.68	35.64
10	35.64	39.6
11	39.6	43.56
12	43.56	47.52

APPROVALS		DATE	TITLE:	
DRAWN	G.M.Chen	2015/5/4	EPELON 德之隆® ELECTRONICS CO.,LTD	
CHECKED			3.96mm Crimp Style Connectors	
APPROVALS			PART NO.	A3960-XXP
TOLERANCES ARE			UNIT: mm	SCALE: 1:1
30 <sup>±0.15</sup>	±0.30	ANGLE		SHEET 1 OF 1
10 <sup>±0.30</sup>	±0.20	±2°	DRAWING NO.	PROJ.
5 <sup>±0.10</sup>	±0.15			
ECN NO.	REV.	DATE.	DESCRIPTION.	
	A		NEW	

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [DEALON](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)  
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)  
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)  
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)  
[803-43-024-10-001000](#)