



Recommended P.C.B Layout

SPECIFICATIONS:

- 1. MATERIAL:
HOUSING: PBT BLACK 30%GF: UL 94V-0
TERMINAL: 110 SERIES COPPER ALLOY T=0.30mm
MATE: TAB=0.8

2. FINISH:

TERMINAL: MATTE Sn PLATED ALLOY COPPER

3. ELECTRICAL

- CONTACT RESISTANCE: 50mΩ Max
- INSULATION RESISTANCE: 100MΩ/500VDC Min
- DIELECTRIC WITHSTANDING VOLTAGE: 500VAC/Minuter
- CURRENT RATING: 15A/250VDC PER CONTACT MIN.
- VOLTAGE RATING: 250VAC/DC (RMS)

4. MECHANICAL:

- DURABILITY: 5000 CYCLES Min INSERTION FORCE: 3.5kgf Max
- EXTRACTION FORCE: 1.0kgf Min ENVIRONMENTAL STORAGE TEMPERATURE: -20°C ~ 85°C

APPROVALS		DATE	DRAWING NO.		SCALE		SHEET		
DRAWN	G.M.Chen	2014/11/26	ELECTRONICS CO.,LTD		1:1		1 OF 1		
CHECKED			CONNECTOR						
APPROVALS			PART NO.	BX503-35					
TOLERANCES ARE			30±0.15	±0.30	ANGLE	±2°	PROJ.		
			10±0.10	±0.20	UNIT: mm				
			5±0.10	±0.15	DRAWING NO.				
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.			
	A		NEW						

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fuse Holder](#) category:

Click to view products by [DEALON](#) manufacturer:

Other Similar products are found below :

[570-290-741P40](#) [0031.1351.01](#) [020417G](#) [020418E](#) [6R30A1B](#) [6SC30A2IC](#) [80910030](#) [8601.2020](#) [G15A2SPQ](#) [9-3557-GP REV A](#) [HDJ-B](#)
[R6J30A3S](#) [HFH-1](#) [RF30A1S](#) [RF30A2B](#) [RF30A3SP](#) [15600-08-10](#) [BK/HHM](#) [HTJ-LES-FUSE](#) [C4044-1](#) [2086-1](#) [2602](#) [2650](#) [178.000100](#)
[F60A2SQ](#) [T30A2B](#) [G4PB8](#) [2660](#) [CQ-209V](#) [HKP-CCHH](#) [R6F30A2S](#) [341001A](#) [345621A](#) [348670](#) [CVRMCC](#) [4202](#) [4407](#) [4408](#) [4413](#) [4423](#)
[4532](#) [4537](#) [TSD1404-12](#) [BPHHU](#) [HPC](#) [55900008011](#) [32NNL](#) [345602-010](#) [345603-010](#) [345612](#)