

Technical Data

Material:

Contact material: Brass
 Plating: Gold Flash
 Insulator material: Black polyester (H94V-0 Standard: PA6T+30%G. F


Electrical:

Current rating: 1.0amps/contact max.
 Contact resistance: $\leq 20m\Omega$ /contact
 Insulation resistance: $\geq 1000M\Omega$ at V=100V
 Withstanding voltage: 300V AC/minute

Mechanical:

Soldering temperature: +260°C, 4s max

UNSPECIFIED TOLERANCE: ± 0.20



PCB Layout

A=1.27*nP ± 0.40
 B=1.27*nP-1.27 ± 0.20

Pin Number=1~50

| APPROVALS | | DATE | DRAWING NO. | | SHEET |
|-----------------|----------|---------------------|-----------------|---------|--------|
| DRAWN | G.M.Chen | 2015/7/17 | DZ127R-11-XX-25 | | 1 OF 1 |
| CHECKED | | | CONNECTION | | |
| APPROVALS | | | | | |
| TOLEFRANCES ARE | | 30 ^{±0.15} | ±0.30 | ANGLE | |
| | | 10 ^{±0.10} | ±0.20 | | |
| | | 5 ^{±0.10} | ±0.15 | ±2° | |
| ECN NO. | REV. | DATE. | DESCRIPTION. | CHANGE. | CHECK. |
| | A | | NEW | | |

DEALON 德之隆®
 ELECTRONICS CO.,LTD

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [DEALON](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [00-9021-0611-00-339](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#)
[70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#)
[FCN-367T-T012/H](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-41-018-10-001000](#)