


Technical Data
 Material:
 Contact material:Brass
 Plating:Gold Flash
 Insulator material:Black polyester UL94V-0
 Standard:6T+30%G.F

Electrical:
 Current rating:1.5Amps/contact_max.
 Contact resistance:≤20mΩ/contact
 Insulation resistance:≥1000MΩ at V=100V
 Withstanding voltage:450V AC/minute

Mechanical:
 Soldering temperature:+260°C, 4s max
 UNSPECIFIED TOLERANCE: ±0.20



PCB Layout

$$A=2.0 * \frac{nP}{2} \pm 0.40$$

$$B=2.0 * \frac{nP}{2} - 2.0 \pm 0.20$$

Pin Number=2~80

APPROVALS		DATE	DRAWING NO.	
DRAWN	G.M.Chen	2015/7/17	D/2200W-22-XX-52	
CHECKED			SHEET 1 OF 1	
APPROVALS			PROJ	
TOLEANCES ARE				
	±0.30	±0.20		
	±0.10	±0.13		
	±0.10	±0.10		
ECN NO.	REV.	DATE.	DESCRIPTION.	
	A		NEW	
			CHANGE.	
			CHECK.	
			APPRO.	

DEALON 德之隆
 ELECTRONICS CO.,LTD

2.00 Pitch 弯插

SCALE: 1:1

PROJ

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [DEALON](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)
[803-43-024-10-001000](#)