



PCB Layout

A=2.54*P±0.50
 B=2.54*nP-2.54±0.20
 Pin Number=1~40

Technical Data
 Material: Brass
 Contact material: Brass
 Plating: Gold Flash
 Insulator material: Black polyester UJ94V-0
 Standard: PBT+30%G. F

Electrical:
 Current rating: 3Amps/contact max.
 Contact resistance: ≤20mΩ/contact
 Insulation resistance: ≥1000MΩ at V=100V
 Withstanding voltage: 550V AC/minute

Mechanical:
 Soldering temperature: +220°C, 4s max

UNSPECIFIED TOLERANCE: ±0.20

APPROVALS		DATE	DRAWING NO.	
DRAWN	G.M.Chen	2015/7/17	D7254R-11-XX-63	
CHECKED			ELECTRONICS CO.,LTD	
APPROVALS		TITLE:	CONNECTOR	
CHANGE.		PART NO.	D7254R-11-XX-63	
CHECK.		UNIT:	mm	
APPRO.		SCALE:	1:1	
DESCRIPTION.		ECN NO.	SHEET 1 OF 1	
NEW		REV.	PROJ.	
A		DATE.		
ECN NO.		REV.	DATE.	

TOLERANCES ARE		ANGLE	DRAWING NO.	
30 ^{±0.15}	±0.30	±2°	D7254R-11-XX-63	
10 ^{±0.10}	±0.20			
5 ^{±0.10}	±0.15			



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [DEALON](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [00-9021-0611-00-339](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#)
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#)
[70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#)
[FCN-367T-T012/H](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)
[803-41-018-10-001000](#)