


2.50 ± 0.15





Technical Data
 Material:
 Contact material:Brass
 Plating:Gold Flash
 Insulator material:Black polyester UL94V-0
 Standard:PA6T+30%G.F

Electrical:
 Current rating:3Amps/contact max.
 Contact resistance: $\leq 20m\Omega$ /contact
 Insulation resistance: $\geq 1000M\Omega$ at V=100V
 Withstanding voltage:550V AC/minute

Mechanical:
 Soldering temperature: $+260^{\circ}C$, 4s max

UNSPECIFIED TOLERANCE: ± 0.20



A PYPE

PCB Layout

A=2.54* n P ± 0.50
 B=2.54* n P-2.54 ± 0.20
 Pin Number=1~40

APPROVALS			DATE	ELECTRONICS CO.,LTD		
DRAWN	G.M.Chen	2015/7/17		CONNECTOR		
CHECKED						
APPROVALS						
PART NO.		D/2254S-11-XX-50		SHEET 1 OF 1		
TITLE:				SCALE: 1:1		
UNIT: mm				DRAWING NO.		
ANGLE		$\pm 2^{\circ}$		PROJ.		
TOLERANCES ARE				PROJ.		
10 \pm 0.10	10 \pm 0.10	10 \pm 0.10				
30 \pm 0.15	30 \pm 0.15	30 \pm 0.15				
5 \pm 0.05	5 \pm 0.05	5 \pm 0.05				
CHANGE.		CHECK.		APPRO.		PROJ.
NEW						
DESCRIPTION.						
ECN NO.						
REV.		DATE.				

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [DEALON](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)
[803-43-024-10-001000](#)