



PCB Layout

Technical Data

Material:
 Contact material: Brass
 Plating: Gold Flash
 Insulator material: Black polyester UL94V-0
 Standard: PA6T+30%G. F

Electrical:

Current rating: 3amps/contact max.
 Contact resistance: $\leq 20m\Omega$ /contact
 Insulation resistance: $\geq 1000M\Omega$ at V=100V
 Withstanding voltage: 550V AC/minute

Mechanical:

Soldering temperature: +260°C, 4s max

UNSPECIFIED TOLERANCE: ± 0.20

$$A = 2.54 * \frac{n^p}{2} \pm 0.50$$

$$B = 2.54 * \frac{n^p}{2} - 2.54 \pm 0.20$$

APPROVALS		DATE	DRAWING NO.				
DRAWN	G.M.Chen	2015/7/17	D/2254S-22-XX-75				
CHECKED			ELECTRONICS CO.,LTD				
APPROVALS			CONNECTOR				
TOLERANCES ARE		30 ^{+0.15} 10 ^{+0.30} 9 ^{+0.10} 5	± 0.30 ± 0.20 ± 0.15 ± 0.10	ANGLE	UNIT: mm	SCALE: 1:1	SHEET 1 OF 1
CHANGE.	CHECK.	APPRO.	DESCRIPTION.		PROJ.		
ECN NO.	REV.	DATE.	NEW				
	A						

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [DEALON](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [0009485154](#) [009176003701906](#) [0050291907](#) [00-9021-0611-00-339](#) [02.125.8002.8](#) [609-3404](#)
[61062-3](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#) [65781-](#)
[047](#) [65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#) [M90C108951C](#) [70.362.1628.0](#)
[70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#) [FCN-367T-](#)
[T012/H](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-014-20-001000](#)