


P.C.B LAYOUT



- 技术指标:
1. 件材料: PA66 (UL-94V-0)
  2. 接触件: 黄铜镀锡
  3. 接触电阻: <10mΩ
  4. 绝缘电阻: >100MΩ
  5. 额定电压: 250V AC DC
  6. 额定电流: 2.0A ACDC
  7. 耐压: 能承受1000V AC/Minute
  8. 工作温度: -25~+85

Pin	A	B	C
2	2.00	6.00	2.5
3	4.00	8.00	2.50
4	6.00	10.00	3.50
5	8.00	12.00	5.50
6	10.00	14.00	7.50
7	12.00	16.00	9.50
8	14.00	18.00	11.50
9	16.00	20.00	13.50
10	18.00	22.00	15.50
11	20.00	24.00	15.50
12	22.00	26.00	15.50
13	24.00	28.00	15.50
14	26.00	30.00	15.50
15	28.00	32.00	15.50

ECN NO.		REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.
		A		NEW			

APPROVALS		DATE
DRAWN	G.M.Chen	2015/7/17
CHECKED		
APPROVALS		

TOLERANCES ARE		ANGLE
30 <sup>±0.15</sup>	±0.30	±2°
10 <sup>±0.10</sup>	±0.20	
5 <sup>±0.05</sup>	±0.10	

TITLE:		CONNECTION	
PART NO.		L200HY-W-XXA	
UNIT: mm	SCALE: 1:1	SHEET 1 OF 1	
DRAWING NO.		PROJ.	

**DEALON** 德之隆®  
ELECTRONICS CO.,LTD

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [DEALON](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)  
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)  
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)  
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)  
[803-43-024-10-001000](#)