



P. C. B LOYOCT

- 技术要求Notes:**
- 1.外观质量Appearance quality:
 - a.金属表面镀层不能有明显损伤: Coating on metal surface can not be damaged obviously;
 - b.塑壳表面不能有明显的变形或开裂: No obvious deformation or cracking can be observed on the surface of the Housing;
 - c.产品表面应保持清洁: Product surface should be kept clean;
 - 2.工作温度 Working temperature: -25℃~+105℃;
 - 3.额定电压 Voltage Rating : Max 250V [AC/Effective value ms)/DC];
 - 4.额定电流 Current Rating: Max 2A [AC/Effective value ms)/DC];
 - 5.接触电阻 Contact resistance: Max 20 mΩ
 - 6.绝缘电阻 Insulation resistance: Min 1000MΩ;
 - 7.耐压 Withstanding voltage: 1000V AC(50 Hz. Effective value: 1 min);
 - 8.环保要求应符合RoHS标准 Environmental requirements should meet RoHS standards.

Pin	A	B	C
2	2.50	10.00	8.30
3	5.00	12.50	10.80
4	7.50	15.00	13.30
5	10.00	17.50	15.80
6	12.50	20.00	18.30
7	15.00	22.50	20.80
8	17.50	25.00	23.30
9	20.00	27.50	25.80
10	22.50	30.00	28.30
11	25.00	32.50	30.80
12	27.50	35.00	33.30
13	30.00	37.50	35.80
14	32.50	40.00	38.30
15	35.00	42.50	40.80
16	37.50	45.00	43.30

ECN NO.		REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.																									
NEW		A																														
<table border="1"> <thead> <tr> <th colspan="2">APPROVALS</th> <th>DATE</th> </tr> </thead> <tbody> <tr> <td>DRAWN</td> <td>G.M.Chen</td> <td>2015/7/17</td> </tr> <tr> <td>CHECKED</td> <td></td> <td></td> </tr> <tr> <td>APPROVALS</td> <td></td> <td></td> </tr> </tbody> </table>								APPROVALS		DATE	DRAWN	G.M.Chen	2015/7/17	CHECKED			APPROVALS															
APPROVALS		DATE																														
DRAWN	G.M.Chen	2015/7/17																														
CHECKED																																
APPROVALS																																
<table border="1"> <thead> <tr> <th colspan="2">TOLERANCES ARE</th> <th>ANGLE</th> <th>SCALE</th> <th>SHEET</th> </tr> </thead> <tbody> <tr> <td>30~40</td> <td>±0.30</td> <td>±2°</td> <td>1:1</td> <td>1 OF 1</td> </tr> <tr> <td>10~30</td> <td>±0.20</td> <td></td> <td></td> <td></td> </tr> <tr> <td>5~10</td> <td>±0.15</td> <td></td> <td></td> <td></td> </tr> <tr> <td>~5</td> <td>±0.10</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>								TOLERANCES ARE		ANGLE	SCALE	SHEET	30~40	±0.30	±2°	1:1	1 OF 1	10~30	±0.20				5~10	±0.15				~5	±0.10			
TOLERANCES ARE		ANGLE	SCALE	SHEET																												
30~40	±0.30	±2°	1:1	1 OF 1																												
10~30	±0.20																															
5~10	±0.15																															
~5	±0.10																															
TITLE: CONNECTOR PART NO.: L254XHB-XXPW UNIT: mm SCALE: 1:1 SHEET 1 OF 1 DRAWING NO.:				DEALON 德之隆 ELECTRONICS CO.,LTD																												

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [DEALON](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)
[803-43-024-10-001000](#)