


Circuit Diagram



P.C.B layout



Specifications:

Insulation resistance	100M ohm Min
Test voltage	AC 500V
Contact resistance	100m ohm Max
Operating force	35±15g

⑦	Shrapnel	1	Beryllium Copper	Natural
⑥	Contact	1	AgNi10	Natural
⑤	Lever	1	Stainless Steel	Natural
④	Terminal	3	Brass(0.60t)	Plating silver
③	Case	1	PBT	White
②	Knob	1	PBT	White
①	Cover	1	PBT	Black

APPROVALS		DATE	DRAWING NO.	
DRAWN	G.M.Chen	2015/5/15	LF-128	
CHECKED			MICRO SWITCHS	
APPROVALS			ELECTRONICS CO.,LTD	

ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.	CHECK.	APPRO.	TOLERANCES ARE	30 ^{±0.15} 10 ^{±0.20} 5 ^{±0.13}	±2'	SCALE: 1:1	SHEET 1 OF 1
	A		NEW				±0.30 ±0.20 ±0.13				PROJ.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Basic / Snap Action Switches](#) category:

Click to view products by [DEALON](#) manufacturer:

Other Similar products are found below :

[5SM901-S12](#) [5SM9-S12N195](#) [602EN532](#) [602EN535-RB](#) [602HE5-RB1](#) [604HE162](#) [604HE223-6B](#) [624HE17-RB](#) [6HM82](#) [6HM89](#) [6SE1](#)
[6SX1-H58](#) [70500216](#) [70599106](#) [71051](#) [MBH2731](#) [79211923](#) [79218589](#) [7AS12](#) [MIL30126AB6BBMD4A12XAU](#) [ML-1155](#) [ML-1376](#)
[831010C3.0](#) [831090C2.EL](#) [83131904](#) [84212012](#) [8AS239](#) [8HM73-3](#) [8SX26-H33](#) [914CE1-6G](#) [PL-100](#) [11SM1077-H4](#) [11SM1077-H58](#)
[11SM1-TN107](#) [11SM405](#) [11SM8423-H2](#) [11SX37-T](#) [11SX48-H58](#) [11SM2442-T](#) [11SM76-T](#) [11SM77-H58](#) [11SM863-T](#) [11SM866](#) [A7CN-](#)
[1M-1-LEFT](#) [A831700C7.0](#) [121EN188-R](#) [1245.0120](#) [125EN56-RB](#) [1267.0101](#) [1267.7101](#)