



Technical Data Material  
 Contact Material: Brass/Phosphor Bronze  
 Contact plating: Nicker/Gold Flash  
 Insulator Material: Black Polyester UL94V-0  
 Standard: PBT

Electrical  
 Current rating: 3.0amps/contact ma  
 Contact resistance: 200m/contact  
 Insulation resistance:  $\geq 1000M\Omega$  at V=100V  
 Withstanding Voltage: 1000V AC/minute  
 Mechanical  
 Operating temperature: -40 Cto+105C

APPROVALS		DATE	DEALON 德之隆® ELECTRONICS CO.,LTD		TITLE:	PART NO.	SCALE:	SHEET
DRAWN	G.M.Chen	2014/8/18			DETECTOR SWITCHES	M254D-02-065-B	1:1	1 OF 1
CHECKED								
APPROVALS								
TOLEFRANCES ARE		30 <sup>±0.15</sup>	±0.30	ANGLE	UNIT: mm	SCALE: 1:1	SHEET 1 OF 1	PROJ.
		10 <sup>±0.10</sup>	±0.20					
		5 <sup>±0.10</sup>	±0.15	±2°	DRAWING NO.			
ECN NO.	REV.	DATE.	DESCRIPTION.		CHANGE.	CHECK.	APPRO.	
	A		NEW					

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [DEALON](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [0009485154](#) [009176003701906](#) [0050291907](#) [00-9021-0611-00-339](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67016-026LF](#) [67095-007LF](#) [68631-112](#) [68645-018](#) [68648-049](#) [699319-000](#)  
[70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5020](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [754199-000](#) [760-3052](#) [787-8014-00](#)  
[FCN-367T-T012/H](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#)  
[803-41-018-10-001000](#)