





2.54±0.15



Technical Data

Material:

- Pin(outer sleeve): Brass,machined CuZn38Pb2
- Plating(outer sleeve):
- Tin plated:2µm/80µ"Ni, 5µm/200µ"Sn
- Gold Plated:2µm/80µ"Ni,Full gold
- Insulator(black): Glass filled thermoplastic polyester
- UL94V-0

Electrical:

- Current rating: 3Amps/contact max.
- Contact resistance: ≤4mΩ/contact
- Insulation resistance: ≥1000MΩ at V=100V
- Operating voltage: 60VAC/DC

Mechanical:

- Operating temperatures: Gold Plated:-55°C to+125°C
- Tin plated:-40°C to+105°C

APPROVALS		DATE	TITLE:	
DRAWN	G.M.Chen	2015/7/17	ELECTRONICS CO.,LTD	
CHECKED			Connector	
APPROVALS			PART NO.	MZ254S-11-XX-10
TOLERANCES ARE		30 ^{±0.15}	ANGLE	
		10 ^{±0.20}	UNIT:	mm
		5 ^{±0.13}	SCALE:	1:1
ECN NO.	REV.	DATE.	DESCRIPTION.	CHANGE.
	A		NEW	
				CHECK.
				APPRO.
				DRAWING NO.
				SHEET 1 OF 1
				PROJ.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Headers & Wire Housings](#) category:

Click to view products by [DEALON](#) manufacturer:

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [644827-2](#) [65495-038](#) [65692-001LF](#)
[65781-018](#) [65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#)
[M90C108951C](#) [70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-](#)
[3052](#) [80.063.4001.1](#) [800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#)
[803-43-024-10-001000](#)