

A

签名
SIGN

变更内容
REVISION NOTES

日期
DATE

版别
REV.

标记
REV. LTR.

规格说明: Specifications:
电气特性: Electrical:

1. 额定电流: Current Rating
1.0A/contact terminal

2. 额定电压: Voltage Rating
30V DC

3. 接触阻抗: Contact Resistance
50 milliohms MAX

4. 耐压: Dielectric Withstanding Voltage:
300 V AC AT Sea Level

5. 绝缘阻抗: Insulation Resistance:
100MEGA ohms MIN

物理性能: Mechanical:

1. 插拔力: Connector Mate and Unmate Force
Mate force: 3.0kgf (MAX)
Unmate force: 0.7kgf (MIN)

2. 端子保持力: Terminal Retention
0.5kgf (MIN)

原材料: Material:

1. 塑胶: Housing:
Hing Temperature Tnermaplastics,
UI 94V-0 LCP Black

2. 端子: Contact: Copper Alloy C2680

3. 外壳: Shell: SUS 304

电镀: Finish:
1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails
2. 外壳: Shell:
Nickel Plating (能过炉自动上锡)

品名
TITLE

料号
PRO. NO.

图号
DWG. NO.

图名
DNG. NAME

版次
REV.

比例
SCALE

表面处理
PLATED

料厚
THICKNESS

材料
MATERIAL

MIRCO USB 5S B TYPE
5.65MM 卷边 短针

XXXXXXXXXX

USB-MR-D-023

德艺隆电子有限公司

绘图
DRAWING

审核
CHECKED

核准
APPROVED

页次 1/1
SHEET

路径
FILE ROUTE

7

6

5

4

3

2

1

8.04

7.40

5.65

5.00

1.98

0.65

0.25

0.45

0.05

0.65

0.55

6.0

2.98

2.60

0.65

0.40

1.50

1.22

1.00

0.65

0.30

4.00

5.65

6.90

3.45

5.65

PIN1

PIN5

PCB EDGE

RECOMMENDED PCB LAYOUT
TOLERANCE: ±0.05

GENERAL TOLERANCES

CALSS	I	II	III
X.XXX	±0.01	±0.02	±0.03
X.XX	±0.03	±0.05	±0.08
X.X	±0.05	±0.10	±0.12
X.	±0.10	±0.15	±0.20
ALGLE	±0.5°	±1.0°	±2.0°

版次	A/0	单位	MM
比例	1:1	单位	MM

页次	1/1	路径	FILE ROUTE
----	-----	----	------------

6

7

E

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [DEALON](#) manufacturer:

Other Similar products are found below :

[950](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBC111M5](#) [MUSBD11135](#) [17-200721](#) [217450-1](#) [KMBVX-TH-5S-B30](#) [896-30-004-00-000000](#)
[KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [SK-60A-2](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [A-USB](#)
[A-2P-C](#) [MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVSCCG](#) [4689-1](#) [1-1734084-2](#) [MUSBC11135](#) [USBF21ZNSCC](#) [USBBFTV6ZC](#)
[MUSBB151341](#) [10135326-001LF](#) [M9177/3-1](#) [TJ-105](#) [USB-A-S-F-B-VT](#) [4198](#) [690-024-633-031](#) [UB-20PMFP-LC7001](#) [USBFTVC6MRG](#)
[UA-20BMFA-SL8001](#) [17-200011](#) [USBFTVC7ZC](#) [UB-20AFMM-LL7A01](#) [USBFTVC2MN](#) [CAP-WCCMLPB1](#) [1310-1031-01](#) [2041386-1](#)
[2274475-3](#) [UB-20BMFA-SL8001](#) [UB-20PMFP-SC8003](#)