



**Specifications:**

**1. Electrical:**

- 1.1 Current Rating: 1.8A/contact terminal
- 1.2 Voltage Rating: 30V DC
- 1.3 Contact Resistance: 50 milliohms Max
- 1.4 Dielectric Withstanding Voltage: 300 V AC AT Sea Level

**2. Mechanical:**

- 2.1 Connector Mate and Unmate Force
  - Mate force: 3.0kgf (Max)
  - Unmate force: 0.7kgf (MIN)
- 2.2 Durability: 2000 cycles
- 3. Material:
  - 3.1 Housing:
    - Hing Temperature Thermoplastics,
    - U1 94V-0 LCP Black
  - 3.2 Contact C5191-EH
  - 3.3 Shell: H65 EH0.3MM
- 4. PLATING:
  - 4.1 Contact: Plated Gold in Mating Area; Tin On Solder Tails
  - 4.2 Shell: Nickel 50u"Min Plated.

REV.	ECN NO	LOCATIONS	DESCRIPTION	DATE

PART NO: A01SBXXXXXXXX1-067	MATERIAL
MODEL NO: XX	FINISH:
UNIT: MM	COLOR:
SIZE: A4	DR:
TOLERANCE UNSPECIFIED	CHK:
.x 0.25	APP:
.xx 0.15	
.xxx 0.10	
Ang. 2'	

德艺隆电子有限公司	
TITLE: MICRO USB 5S B TYPE 四脚全插(牛角型)短针	
REV: A	
SCALE: 5:1	DATE: 2012.05.02

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [USB Connectors](#) category:*

*Click to view products by [DEALON](#) manufacturer:*

Other Similar products are found below :

[950](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBC111M5](#) [MUSBD11135](#) [17-200721](#) [217450-1](#) [KMBVX-TH-5S-B30](#) [896-30-004-00-000000](#)  
[KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [SK-60A-2](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [A-USB](#)  
[A-2P-C](#) [MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVSCCG](#) [4689-1](#) [1-1734084-2](#) [MUSBC11135](#) [USBF21ZNSCC](#) [USBBFTV6ZC](#)  
[MUSBB151341](#) [10135326-001LF](#) [M9177/3-1](#) [TJ-105](#) [USB-A-S-F-B-VT](#) [4198](#) [690-024-633-031](#) [UB-20PMFP-LC7001](#) [USBFTVC6MRG](#)  
[UA-20BMFA-SL8001](#) [17-200011](#) [USBFTVC7ZC](#) [UB-20AFMM-LL7A01](#) [USBFTVC2MN](#) [CAP-WCCMLPB1](#) [1310-1031-01](#) [2041386-1](#)  
[2274475-3](#) [UB-20BMFA-SL8001](#) [UB-20PMFP-SC8003](#)