

1	2	3	4	5	6	7	8	9	10
F	E	D	C	B	A				
<p>0.207.05(16X)</p> <p>1.80(2X)</p> <p>0.80(2X)</p> <p>8.94</p> <p>6.5</p> <p>8.34^{+0.08}/_{-0.02}</p> <p>6.69</p> <p>11.24</p> <p>2.563.04</p> <p>0.70</p> <p>1.60</p> <p>0.70</p> <p>1.20</p> <p>2.10</p> <p>4.00</p> <p>3.16</p> <p>1.60</p> <p>0.80</p> <p>4.60</p> <p>4.45</p> <p>0.72.05</p> <p>1.202.05</p> <p>0.70</p> <p>SECTION:A-A</p> <p>RECOMMENDED PCB LAYOUT(TOP VIEW)</p> <p>THICKNESS: 0.80MM;DEFAULT TOLERANCE:±0.05</p>									
<p>NOTE:</p> <ol style="list-style-type: none"> MATERIAL SPECIFICATION: <ol style="list-style-type: none"> HOUSING:HIGH TEMPERATURE RESISTANT PLASTIC,UL94 V-0. CONTACTS:COPPER ALLOY MID PLATE: STAINLESS STEEL FRONT SHELL: STAINLESS STEEL PLATING SPECIFICATION: <ol style="list-style-type: none"> CONTACTS: <ol style="list-style-type: none"> 50μ" MIN. UNDER PLATED OVER ALL. AU PLATED ON THE FUNCTIONAL AREA OF CONTACT. (GOLD PLATING THICKNESS FOLLOW THE P/N) FRONT SHELL: <ol style="list-style-type: none"> 30μ" MIN. UNDER PLATED OVER ALL. MID PLATE: CLEAR ONLY MECHANICAL PERFORMANCE. <ol style="list-style-type: none"> INSERTION FORCE: 0.5~1.5kgf. REMOVAL FORCE: 0.8kgf~1.5kgf. DURABILITY: 5000 CYCLES. ELECTRICAL PERFORMANCE. <ol style="list-style-type: none"> CURRENT RATING:3.0A VOLTAGE RATING:5.0V LLCR: <ol style="list-style-type: none"> VBUS & GND PINS AND OTHER PINS: 40mΩ/PIN MAX. SHIELD: 50mΩ/MAX. LLCR MAX. CHANGE OF ALL PINS: 10mΩ. INSULATION RESISTANCE: 100MΩ MIN DIELECTRIC WITHSTAND VOLTAGE,AC 100V FOR 1 MINUTE. ENVIRONMENTAL PERFORMANCE: <ol style="list-style-type: none"> OPERATING TEMPERATURE: -25~+85℃. REFLOW: THE PEAK TEMPERATURE ON THE BOARD SHALL BE MAINTAINED FOR 10 SECONDS AT 260°C. 									
<p>REV. ECN NO. DESCRIPTION APP. DATE</p> <p>A</p>									
<p>DONGDUAN DEALON ELECTRONICS CO.,LTD</p> <p>TITLE : TYPE-C 16PIN 单排 沉板1.6mm L=6.5mm</p> <p>PARTS NO. : USB-TYPE-C-016</p> <p>DWG NO. :</p> <p>TONY</p> <p>JACK</p> <p>DAVID</p> <p>SIZE A4 SCALE 1:1 SHEET 1 of 1 REV. A</p>									
<p>UNIT : mm</p> <p>TOLERANCES 一般公差</p> <p>DISTANCE X. ±0.30 .X ±0.25 .XX ±0.15 .XXX ±0.10</p> <p>ANGLE X' ±2' .X' ±1' .XX' ±0.5'</p>									
<p>THIS PRODUCT SHOULD MEET HAZARDOUS MATERIAL CONTROL DIRECTIVE OF JUN SHENG JIE FROM RAW MATERIAL TO MANUFACTURING, PACKAGE AND DELIVERY.</p>									
<p>JSL frame_C Rev. A 2016/08/17</p>									

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [DEALON](#) manufacturer:

Other Similar products are found below :

[950](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBC111M5](#) [MUSBD11135](#) [17-200721](#) [217450-1](#) [KMBVX-TH-5S-B30](#) [896-30-004-00-000000](#)
[KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [SK-60A-2](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [A-USB A-2P-C](#)
[MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVSCCG](#) [4689-1](#) [1-1734084-2](#) [MUSBC11135](#) [USBF21ZNSCC](#) [USBBFTV6ZC](#) [MUSBB151341](#)
[10135326-001LF](#) [M9177/3-1](#) [TJ-105](#) [USB-A-S-F-B-VT](#) [4198](#) [690-024-633-031](#) [UB-20PMFP-LC7001](#) [USBFTVC6MRG](#) [UA-20BMFA-](#)
[SL8001](#) [17-200011](#) [USBFTVC7ZC](#) [UB-20AFMM-LL7A01](#) [USBFTVC2MN](#) [CAP-WCCMLPB1](#) [1310-1031-01](#) [2041386-1](#) [2274475-3](#) [UB-](#)
[20BMFA-SL8001](#) [UB-20PMFP-SC8003](#) [914-614A2025S10200](#)