

1	2	3	4	5	6	7	8	9	10
REV. ECN NO. DESCRIPTION APP. DATE		A							
<p>NOTE:</p> <p>1.MATERIAL SPECIFICATION: 1.HOUSING:HIGH TEMPERATURE RESISTANT PLASTIC,UL94 V-0. 2.CONTACTS:COPPER ALLOY 3.MID PLATE: STAINLESS STEEL 4.FRONT SHELL: STAINLESS STEEL</p> <p>2.PLATING SPECIFICATION: 2-1.CONTACTS: Ni 50u" MIN. UNDER PLATED OVER ALL. Au PLATED ON THE FUNCTIONAL AREA OF CONTACT. PRODUCT EDGE(GOLD PLATING THICKNESS FOLLOW THE P/N) 2-2.FRONT SHELL: Ni 30u" MIN. UNDER PLATED OVER ALL. 2-3.MID PLATE: CLEAR ONLY 3.MECHANICAL PERFORMANCE, 3-1.INSERTION FORCE: 0.5~1.5kgf. 3-2.REMOVAL FORCE: 0.8kgf~1.5kgf. 3-3.DURABILITY: 5000 CYCLES. 4.ELECTRICAL PERFORMANCE, 4-1. CURRENT RATING:3.0A VOLTAGE RATING:5.0V 4-2. LLCR: VBUS & GND PINS AND OTHER PINS: 40mΩ/PIN MAX. SHIELD: 50mΩ/MAX. LLCR MAX. CHANGE OF ALL PINS: 10mΩ. 4-3.INSULATION RESISTANCE: 100MΩ MIN 4-4.DIELECTRIC WITHSTAND VOLTAGE:AC 100V FOR 1 MINUTE. 5. ENVIRONMENTAL PERFORMANCE: OPERATING TEMPERATURE: -25℃~+85℃. 6.IR REFLOW: THE PEAK TEMPERATURE ON THE BOARD SHALL BE MAINTAINED FOR 10 SECONDS AT 260°C.</p>									
<p>RECOMMENDED PCB LAYOUT(TOP VIEW) THICKNESS: 0.80MM;DEFAULT TOLERANCE:±0.05</p>									
<p>UNIT : mm</p> <p>TOLERANCES 一般公差</p> <p>DISTANCE X. ±0.30 .X ±0.25 .XX ±0.15 .XXX ±0.10</p> <p>ANGLE X° ±2° .X° ±1° .XX° ±0.5°</p>									
<p>DONGDUAN DEALON ELECTRONICS CO.,LTD</p> <p>TITLE : TYPE-C 16PIN 单排 沉板 0.8mm L=6.5mm</p> <p>PARTS NO. : USB-TYPE-C-021</p> <p>DWG NO. :</p> <p>TONY DRAWN</p> <p>JACK CHECKED</p> <p>DAVID APPROVE</p> <p>SCALE 1:1 SHEET 1 of 1 REV. A</p>									
<p>THIS PRODUCT SHOULD MEET HAZARDOUS MATERIAL CONTROL DIRECTIVE OF JUN SHENG JIE FROM RAW MATERIAL TO MANUFACTURING, PACKAGE AND DELIVERY.</p>									
<p>JSL frame_C Rev. A 2016/08/17</p>									

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [USB Connectors](#) category:

Click to view products by [DEALON](#) manufacturer:

Other Similar products are found below :

[950](#) [A-USB B-TOP-C](#) [MUSBA511N5](#) [MUSBC111M5](#) [MUSBD11135](#) [17-200721](#) [217450-1](#) [KMBVX-TH-5S-B30](#) [896-30-004-00-000000](#)
[KUSBX-AS2N-W](#) [KUSBX-SMT2AP1S-W30](#) [935](#) [957](#) [30-498-6](#) [SK-60A-2](#) [1734082-1](#) [30-1574](#) [30-470](#) [30-489](#) [30-541](#) [30-572-3](#) [A-USB](#)
[A-2P-C](#) [MIKROE-1451](#) [USBFTV2PEM2G](#) [USBFTVSCCG](#) [4689-1](#) [1-1734084-2](#) [MUSBC11135](#) [USBF21ZNSCC](#) [USBBFTV6ZC](#)
[MUSBB151341](#) [10135326-001LF](#) [M9177/3-1](#) [TJ-105](#) [USB-A-S-F-B-VT](#) [4198](#) [690-024-633-031](#) [UB-20PMFP-LC7001](#) [USBFTVC6MRG](#)
[UA-20BMFA-SL8001](#) [17-200011](#) [USBFTVC7ZC](#) [UB-20AFMM-LL7A01](#) [USBFTVC2MN](#) [CAP-WCCMLPB1](#) [1310-1031-01](#) [2041386-1](#)
[2274475-3](#) [UB-20BMFA-SL8001](#) [UB-20PMFP-SC8003](#)