



Recommend PCB Layout

技术指标:

1. 塑件表面应光洁、无毛边、无明显收缩、缺陷、裂纹等现象。
2. 工作温度:  $-25^{\circ}\text{C} \sim 85^{\circ}\text{C}$ 。
3. 适用线规: AWG#30~#22
4. 额定电压: 250V DC/AC(rms)。
5. 额定电流: 3.0A
6. 接触电阻:  $\leq 20\text{m}\Omega$
7. 耐压值: 1000V AC/minute。
8. 绝缘电阻:  $\geq 1000\text{M}\Omega$ 。

Poles	Dimensions (mm)	
	A	B
1	2.50	7.50
2	2.50	7.50
3	5.00	10.00
4	10.00	12.50
5	10.00	15.00
6	12.50	17.50
7	15.00	20.00
8	17.50	22.50
9	20.00	25.00
10	22.50	27.50
11	25.00	30.00
12	27.50	32.50
13	30.00	35.00
14	32.50	37.50
15	35.00	40.00
16	37.50	42.50

APPROVALS		DATE										
DRAWN	G.M.Chen	2015/7/17										
CHECKED												
APPROVALS												
TITLE:		Connector										
PART NO.	XH-□□AW											
UNIT: mm	SCALE: 1:1	SHEET 1 OF 1										
DRAWING NO.		PROJ.										
ECN NO.	REV.	DATE.	DESCRIPTION.									
	A		NEW									
CHANGE. CHECK. APPRO.												
<table border="1" style="width: 100%;"> <tr> <td>30<sup>±0.15</sup></td> <td>±0.30</td> <td>ANGLE</td> </tr> <tr> <td>10<sup>±0.10</sup></td> <td>±0.20</td> <td></td> </tr> <tr> <td>5<sup>±0.05</sup></td> <td>±0.15</td> <td>±2°</td> </tr> </table>				30 <sup>±0.15</sup>	±0.30	ANGLE	10 <sup>±0.10</sup>	±0.20		5 <sup>±0.05</sup>	±0.15	±2°
30 <sup>±0.15</sup>	±0.30	ANGLE										
10 <sup>±0.10</sup>	±0.20											
5 <sup>±0.05</sup>	±0.15	±2°										
TOLERANCES ARE												

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Headers & Wire Housings](#) category:*

*Click to view products by [DEALON](#) manufacturer:*

Other Similar products are found below :

[57102-F02-18ULF](#) [58102-G61-06LF](#) [582553-1](#) [009176003701906](#) [01.001.5753.1](#) [0050291907](#) [02.125.8002.8](#) [609-3404](#) [61062-3](#)  
[CSU011177004](#) [622-0430](#) [622-3653LF](#) [63453-116](#) [636-1030](#) [636-1427](#) [636-3427](#) [636-4007](#) [641938-9](#) [65495-038](#) [65692-001LF](#) [65781-018](#)  
[65781-047](#) [65817-010LF](#) [65817-015LF](#) [66207-023LF](#) [67095-007LF](#) [67601157](#) [68631-112](#) [68645-018](#) [699319-000](#) [M90C108951C](#)  
[70.362.1628.0](#) [70-4210](#) [70-4226B](#) [70-4853B](#) [707-5028](#) [71.350.2428.0](#) [71961-016LF](#) [733-134](#) [733-162](#) [754199-000](#) [760-3052](#) [80.063.4001.1](#)  
[800-90-001-10-001000](#) [800-90-010-10-002000](#) [801-43-002-10-013000](#) [801-43-006-10-002000](#) [803-41-018-10-001000](#) [803-43-024-10-](#)  
[001000](#) [803-93-012-10-001000](#)