



Technical characteristics:

- Specifications**
 DIN EN 60 664-1
 DIN EN 61 984
- Inserts**
01. Number of contacts :24+PE
 02. Rated Current :16A
 03. Rated Voltage :500V
 04. Pollution degree :3
 05. Rated impulse voltage :6kv¹⁰
 06. Insulation resistance :≥10Ω
 07. Material:Polycarbonate
 08. Rated voltage acc. to UL/CSA:600V
 09. Limiting temperatures : -40℃~+125℃
 10. Flammability acc. to UL94:V0
 11. Mechanical working life (mating cycles) : ≥500

- Contacts**
01. Material:Copper alloy
 02. Surface:hard-silver plated
 03. Contact resistance : ≤1mΩ
 04. Terminal :Crimp terminal
 05. Wire gauge :0.14-4.0mm² (AWG 26-12)
 06. Stripping length :7.5mm
 07. Rohs Compliance

Note:Crimp contact pins should order separately

PART NO. /		DEGSON® 宁波高松电子有限公司	
APPD: HYS 2016.9.6	NAME: NINGBO DEGSON ELECTRICAL CO., LTD		
CHKD: Ljm 2016.9.5	TITLE: CUSTOMER DRAWING DE-024-MC		
DRFT: Mr.Yang 2016.08.08	DRAWING NO. /		
THIRD ANGLE PROJECTION		REV	DO
DO NOT SCALE DRAWING		SHEET	1/1
SCALE		SCALE	1:1

REVISION RECORD				
REV	ECN	DESCRIPTION	DRFT	DATE

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Standard Circular Connector](#) category:

Click to view products by [Degson](#) manufacturer:

Other Similar products are found below :

[C015](#) [10F006](#) [001](#) [1](#) [5M2530B10P](#) [600247N007](#) [600259N006](#) [600273N007](#) [600432N009](#) [6280-2PG-519](#) [6280-3PG-311](#) [6280-3SG-311](#)
[6280-7SG-3DC](#) [6280-7SG-522](#) [6282-5PG-311](#) [6282-6PG-519](#) [6282-8SG-311](#) [6283-11](#) [6283-15](#) [6290](#) [6293](#) [6382-2PG-311](#) [6382-2PG-3DC](#)
[6382-2SG-321](#) [6382-2SG-3DC](#) [6382-4SG-516](#) [67-03E20-37P](#) [681-PMG](#) [CXS3102A14S2P](#) [CXS3102A181S](#) [CXS3106A14S6S](#)
[D38999/20FC8SA L/C](#) [MB12P-1](#) [MB12R-6](#) [7251-2PG-300](#) [7251-2SG-300](#) [7251-4PG-300](#) [7251-4SG-300](#) [7251-5PG-300](#) [7251-5SG-300](#)
[7251-6SG-300](#) [7251-7PG-300](#) [7251-8PG-300](#) [7271-6SG-300](#) [7282-3PG-300-CH3](#) [73000005663](#) [75-190011-03P](#) [75-190216-08S](#) [75-190218-](#)
[10P](#) [75-214636-52P](#) [75-474118-10P](#) [75-474211-03P](#) [75-474218-19S](#)