

**CAUTION
CONTAINS PARTS AND
ASSEMBLIES SUSCEPTIBLE TO
DAMAGE BY ELECTROSTATIC
DISCHARGE (ESD)**



Item # 06770

descoindustries.com

Warns repair people that ESD precautions are required when opening.

MIL-STD-1686C states "Equipment containing ESDS parts and assemblies shall be marked with the (ESD susceptibility) symbol. The symbol shall be located on the exterior surface of the equipment and readily visible to personnel prior to gaining access to ESDS parts and assemblies within the equipment. The following ESD caution statement should be paced adjacent to the RS-471 symbol: "CAUTION, CONTAINS PARTS AND ASSEMBLIES SUSCEPTIBLE TO DAMAGE BY ELECTROSTATIC DISCHARGE (ESD)." (Ref. paragraph 5.7.2)

Per ANSI/ESD S8.1 section 3.1 ESD Susceptibility Symbol Application states 1 "The ESD susceptibility symbol should be used on assemblies and devices that have a sensitivity to ESD events." and, "The symbol may be incorporated on a sticker used to close or seal ESD protective packaging to indicate that materials inside the package are ESD susceptible.

Per ANSI/ESD S20.20 Paragraph 6.2.5.1. ESDS Assemblies and Equipment "ESDS assemblies and equipment containing ESDS parts and assemblies should be marked with an ESD caution symbol located in a position readily visible when an ESDS assembly is incorporated into its next higher assembly."

The user must determine the suitability for use of a Label for his particular application. For best results, Label inventory should be continually replenished. It is recommended that rolls of Labels be stored flat and rotated (flipped over to the other side) periodically. Label rolls should be stored in a dry, well ventilated room with a reasonably consistent temperature of 68°F (20°C) and be protected from exposure to direct sunlight. Labels should not be stored in ultraviolet sunlight, moisture, or heat.

Label rolls over one year old should be evaluated by the user to determine acceptability for the user's application. Desco Industries, Inc. recommends those tracking useful life of product to use shipping/invoice date as Desco Industries, Inc. expressly warrants that for a period of one (1) year from the date of purchase, Desco Labels will be free of defects in material (parts) and workmanship (labor). See details of Limited Warranty online at Desco.com/Warranty.aspx

COLOR: Yellow with black printing

PACKAGED: 500 per roll, 3" diameter core, Date/Lot Coded for QC Traceability

Pressure sensitive labels are designed to call immediate attention to items that are susceptible to damage from ESD. The permanent adhesive labels are designed for use on packages, containers, and anywhere a permanent warning is required. Labels are coated with varnish for added durability.

PAPER SPECIFICATIONS:

Facestock: 60# SemiGloss Litho
Adhesive: B-82
Liner: 40# RL

INK & VARNISH SPECIFICATIONS:

Water Resistance: Excellent
Grease Resistance: Excellent
Alcohol Resistance: Excellent

Item	Description	Qty/Roll
06770	3/4" x 2"	500

RoHS Compliance Statement

None of the following materials are intentionally added in manufacturing this product: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE) as outlined in the Directive 2002/95/EC Article 4.1. See Desco Industries Inc. letter on-line at Desco.com.

Unless otherwise noted, tolerance is ± 10%

Specifications and procedures subject to change without notice.



Made in the United States of America

LABEL, EQUIPMENT CONTAINING



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com
PHONE (909) 627-8178 FAX (909) 627-7449

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407
PHONE (781) 821-8370 FAX (781) 575-0172

**DRAWING
NUMBER**
06770

DATE:
June
2021

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Labels and Industrial Warning Signs](#) category:

Click to view products by [Desco](#) manufacturer:

Other Similar products are found below :

[FTP-020P0704](#) [QC101](#) [QC105](#) [QCC613](#) [QCC615](#) [132465](#) [142810](#) [15288](#) [15425](#) [18511](#) [1878678-5](#) [HTS795-1](#) [30288](#) [1768021-2](#) [18432](#)
[1878679-3](#) [2-1878614-6](#) [PTL-31-427-YL](#) [30239](#) [QC154](#) [QCC612](#) [30545](#) [35070](#) [WM-15-PK](#) [WM-20-PK](#) [5-1768021-6](#) [06770](#) [111852](#)
[111932](#) [KMT-02513V-9](#) [8-1768039-4](#) [1878983-4](#) [B422 25X85MM](#) [PAXLBK10](#) [LAT-52-361-1](#) [PTL-20-486](#) [PTL-38-486](#) [13903](#) [11237](#)
[18389](#) [18341](#) [18603](#) [29904](#) [18519](#) [18524](#) [115110](#) [11199](#) [18542](#) [62351](#) [90731](#)