

Installation Instructions:

Attach top part of cover to chair back and bottom part of cover (with grounding chain attached) to chair seat. Make sure cover is fitted, centered, and secured to chair. Secure the ground chain to center post underneath chair with hook and loop and make sure ground chain makes contact with ESD floor. A minimum length of 6 inches of chain should make contact with the floor. For chairs with wheels make sure the chain is clear of the wheels so that it does not become entangled with the wheels.

Technical Information from ESD Association:

"Fabric upholstered chairs accomplish this by using conductive fibers woven into the fabric. The fabric is then connected through the components of the chair, through the cylinder, base and casters (or drag chain) to the floor." [ESD Handbook ESD TR20.20 Seating section 5.3.5.2 Types and Selection]

If not otherwise noted, tolerance ±10%

Specifications and procedures subject to change without notice



Description:

Desco's Statshield® chair cover is a low charging, dissipative (1 x10⁶ <1 x 10⁹ ohms) material designed to convert a standard chair into an ESD version. The Statshield® chair cover is made from a polyester/cotton blend fabric with BASF carbon suffused mono-filament nylon. The chair back and seat are connected to a drag chain with a 1 megohm resistor that enables the chair cover to be grounded when used on a conductive floor or mat. Desco's Statshield® chair covers are machine washable.

Specifications:

Grounding

resistance: 1 megohm hermetically sealed resistor

Chain Length: 24" long chain with current limiting resistor in series

Fabric Weight: 5 oz per square yard

Fabric Content: 65% polyester, 34% cotton, and 1% BASF

carbon suffused mono-filament nylon

Fabric Color*: Royal Blue

Carbon

Mono-filament: Conductive at $< 1 \times 10^5$ ohms, non-flaking and

non-sloughing

Surface Resistance

of Fabric: 1 x 10⁶ to < 1 x 10⁹ ohms tested per ESD TR53 Seating test based on ANSI/ESD STM12.1, Seating - Resistive Measurement

Static Decay Rate: 5000 volts to 500 volts in less than 0.01

seconds, per FTMS-101C

Size:

Seat: 18" x 20", maximum diameter 19" nominal

Back: 15 1/2" x 18 1/2", maximum diameter 17" nominal

Marking: Product marked with ESD protective symbol to identify used

for ESD control

Laundering Instructions:

The conductive fibers are sensitive to heat and should not be exposed to laundering heat in excess of 120°F. Under normal use and recommended washing conditions, Desco chair covers will maintain their usefulness and effectiveness for a minimum of 25 washings.

Use cool water, with a maximum temperature 120 °F. DO NOT BLEACH. Use only non-ionic softeners and detergents when laundering (Desco recommends Woolite®). For washing with standard house machines use the gentle cycle. For washing with industrial machines, a "Pony" (typically under 200 pound loads) machines must be used. It is not recommended to launder in heavy industrial laundry machines as it will lead to premature wear. Tumble dry using low heat.



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: <u>Desco.com</u> PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370

DRAWING NUMBER 07200 DATE March 2016



^{*}Fabric lots vary slightly in color.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Enclosures, Boxes, & Cases category:

Click to view products by Desco manufacturer:

Other Similar products are found below:

CR-425 PAINTED 585-R-WH-PK M-10-PLATED 60221-01 60566-01-000 HPL-9VB BATT DOOR M-16-LID-PLATED M18-PLTD M-21-LID-PLATED M-21-PLATED M-23-PLATED CU-281-MB 6711GSKT 71884-29-028 LH45-100 Black 7200B 72868-510-000 CNS-0000 Black 72883-510-000 CNS-0101 Black 72906-510-000 CNS-0407 Black 73091-510-000 CNM-0000-BLACK Kit 73092-510-000 CNM-0101 Black 73108-510-000 CNL-0303 Black 73395-510-039 CNS-0006 Bone 74257-510-000 CNL-0004 MDC-1183-PLAIN-ALUM MDC-1183-PTD MDC-13104-PLAIN-ALUM MDC-211 - PAINTED IVORY/BEIGE MDC-321-PTD MDC-432-PLAIN-ALUM MDC-973-PTD 76 77153-01-028 FLX6030 83535-01-508 PS-11296-G PS-11298-B 116-508 120-407 120-412 120-909 120-455 R272-100-000 120-910 R501-001-010 R508-080-000 R508-160-000 R530-120-000 R530-120-000 R531-160-000 R531-200-000 R582-080-100