

- A. Outer conductive layer (10<sup>5</sup> RTT)
- B. Inner non-marking neoprene layer
- C. Reinforced with 4.3 oz. polyester mesh scrim layer
- D. .060" thick, 1 1/4" wide contact area
- E. 30" long, 3/8" wide, 8 string black conductive ribbon
- F, G. 3/4", double sided hook and loop material, for quick and easy attachment to foot.

	Inner (Rust) Layer	Outside (Black) Layer	Test Method
Electrical Characteristics:			
Charge Decay		Less than 0.01 sec.	FTMS-1018, Method 4046
Conductivity		8x10 <sup>3</sup> Ohms/sq.	RMA-808
RTG w/1 megohm resistor		1.3x10 <sup>6</sup> Ohms max.	EOS/ESD-S4.1 @ 100V
RTG w/2 megohm resistor		2.3x10 <sup>6</sup> Ohms max.	EOS/ESD-S4.1 @ 100V
RTT		2 x10 <sup>5</sup> Ohms max.	EOS/ESD-S4.1 @ 100V
Specifications:			
Abrasion	800 cycles	3000 cycles	ASTM-D3389 Method B
Hardness	70 Shore A	70 Shore A	ASTM-D2240
Elongation	600%	400%	ASTM-D412
Tensile	900lbs.	2500lbs.	ASTM-D412

## Note:

One heel grounder on each foot is recommended for proper grounding. Operator is grounded when heel is in contact with grounded dissipative or conductive flooring. Desco recommends the use of foot ground tester 19252. Ask for Technical Bulletin TB-2040. For additional information on the use and maintenance of heel grounders please ask for Technical Bulletin TB-2020.

Meets the requirements of JEDEC-108/9, MIL-HDBK-263A, MIL-STD-1686, DOD-STD-2000.

07560 with 1 megohm resistor

Specifications and procedures subject to change without notice.



FOOT GROUND, HEEL, ADJUSTABLE

DESCO WEST:3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com PHONE (909) 627-8178 FAX (909) 627-7449 FAX REQUEST (909) 627-7126

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370 FAX (781) 575-0172

DRAWING NUMBER 07560 DATE: March 2010

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antistatic Control Products category:

Click to view products by Desco manufacturer:

Other Similar products are found below:

13020 13490 13870 13879 13881 13883 13882 14404 2202SP 3039 37061 42470 09060 09857 42516 37059 04563 17252 19691 19695 09037 09826 09813 66070 100816 68101 68103 98132 73741 13868 13485 13457 13245 13468 13420 13332 13205 13135 91070 8031 8523 66085 40931 37081 13080 13215 13806 73749 010-0225 17260