



Key:

- A. Two layer rubber composite material. Material consists of a layer which provides a non-marring interior surface that will not blemish shoes and a black conductive layer to ground via ESD flooring.
- B. Non-marring inner layer.
- C. 24" conductive ribbon.
- D. One megohm fully insulated current limiting resistor.
- E. Hook and loop adjustable closure.
- F. Elastic material for comfort.

Meets the requirements of ANSI/ESD S20.20, JEDEC-108/9, MIL-HDBK-263A, MIL-STD-1686, DOD-STD-2000.

Electrical Properties are not humidity dependent meeting ANSI/ESD S20.20 flooring/footwear required limit $<3.5 \times 10E7$ ohms tested at 12% and 50% relative humidity per ESD SP9.2

Caution: The foot grounder is for ESD control. It will not reduce or increase your risk of receiving electric shock when using or working on electrical equipment.

	Non-Marking Inner Layer	Black Outer Layer	Test Method
Electrical Properties:			
Charge Decay	< 0.01 sec.	<0.01 sec.	FTMS-1018, Method 4046
RTG w/1 megohm resistor	<10 megohm	<10 megohm	ESD SP.92
Physical Properties:			
Abrasion, 1000 grams, 4000 cycles	<1.0 grams loss	<0.1 grams loss	ASTM-D3389 Method B
Hardness	65 ± 5 Shore A	65 ± 5 Shore A	ASTM-D2240

Note:
 "ESD protective footwear is designed to reduce body charge levels by supplying a conductive path from the body to the floor material. Heel and toe grounders shall be worn on both feet to insure effective use.

The ability of footwear to remove a charge from a charged person who moves from an unprotected area to a protected one, or moves about on an ESD floor should be evaluated. As a person contacts an ESD floor material with static control footwear, the body charge should dissipate leaving minimal residual charge. (ESD Handbook ESD TR20.20-2008 section 5.3.3.3.4 Footwear Proper Usage)

Desco recommends the use of foot ground tester item No. [19252](#), [19276](#), and [19277](#). For additional information on the use and maintenance of foot grounders please ask for Technical Bulletins [TB-2020](#), [TB-2040](#), and [TB-3034](#).

One Megohm Economy Heel Grounder



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710
 WEB SITE: www.Desco.com
 PHONE (909) 627-8178 FAX (909) 627-7449 FAX REQUEST (909) 627-7126

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407
 PHONE (781) 821-8370 FAX (781) 575-0172

DRAWING NUMBER:
 07588

DATE:
 March 2010

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Antistatic Control Products](#) category:

Click to view products by [Desco](#) manufacturer:

Other Similar products are found below :

[13020](#) [13490](#) [13870](#) [13879](#) [13881](#) [13883](#) [13882](#) [14404](#) [2202SP](#) [3039](#) [37061](#) [42470](#) [09060](#) [09857](#) [42516](#) [37059](#) [04563](#) [17252](#) [19691](#)
[19695](#) [09037](#) [09826](#) [09813](#) [66070](#) [100816](#) [68101](#) [68103](#) [98132](#) [73741](#) [13868](#) [13485](#) [13457](#) [13245](#) [13468](#) [13420](#) [13332](#) [13205](#) [13135](#)
[91070](#) [8031](#) [8523](#) [66085](#) [40931](#) [37081](#) [13080](#) [13215](#) [13806](#) [73749](#) [010-0225](#) [17260](#)