

Beige, Blue, White, Grey

Disclaimer:

All statements, technical data, and recommendations contained herein are based upon tests we believe to be reliable. However, the accuracy or completeness thereof is not guaranteed. The proper and correct applications of products and data is the responsibility of the user. Statements or recommendations not contained herein shall have no force or effect unless embodied in a written agreement signed by authorized officers of Desco Industries, Inc.

RoHS 2 and REACH Statement

None of the RoHS 2 restricted materials or REACH substances of very high concern are intentionally added in manufacturing this product. Ref: European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE.

Limited Lifetime Warranty:

Desco warrants for one year that Micastat[®] dissipative laminate products will be free of defects in materials and workmanship and will guarantee dissipative / conductive laminate properties for the life of the product. Damage to laminate caused by misuse of any kind, including using inappropriate cleaners is not covered by <u>Desco Limited Warranty</u>.

**Tolerance for Kits Only: Width ± 0.250" Length ± 0.250" Thickness ±10%

Matting materials have a tendency to shrink slightly when first unrolled. In applications where length is critical, allow the material to relax for at least 4 hours before cutting to size. Using care, always trim with a sharp knife or razor blade.

***Tolerance for Sheets Only:

Published Sheet sizes are oversized typically by 34" to 1.0" in both width and length directions Published Dimensions are \pm 0.250"

Specifications and procedures subject to change without notice.



Description:

Micastat[®] is a static dissipative high pressure thermoset amino resin laminate. It is designed to provide a path to ground and eliminate static charge generation when used as a worksurface. The surface resistance (<1 x 10⁹ ohms Rtg) meets ANSI/ESD S20.20 worksurface required limit for contact with ESD susceptible items. The conductive layer of Micastat[®] laminate is a uniform conductive layer that creates a consistent path-to-ground. Micastat[®] resists hot solder, most solvents and exceeds NEMA standards for wear resistance.

Electrical Properties:

Because the electrical properties of many high pressure laminates have some degree of humidity dependence, all high pressure laminate materials should be carefully tested for adequate performance at low humidity prior to selection and installation.

Property	Value	Test Method
Rtg:	< 1 x 10 ⁹ ohms	ANSI/ESD S4.1 and ESD TR53
RVOL:	< 1 x 10 ⁸ ohms	ASTM-D257
Charge Decay:	<0.009 seconds	FTMS-101C, Method 4046

Measured at 50% and 12% relative humidity. Test reports available upon request.

Specifications:

•	
Construction:	High pressure thermoset amino resin laminate
Thickness:	Nominal 0.038" (0.96mm)
Colors:*	Beige, Blue, White, Grey
Тор:	Non-glare matte finish.
Radius:	1.5" radius corner
Surface:	Top - non-glare matte finish
Post Forming:	5/8" radius, NEMA LD 3.14
Weight:	0.31 lbs/sq ft (0.151 grams/cm ²)
Abrasion Resistance:	Exceeds NEMA LD 3-3.01 Standards
Chemical Resistance:	Unaffected by most solvents
Heat Resistance:	NEMA LD 3-3.06, 160°F (71°C) continuous

*Color and texture may vary between lots and mills.

Grounding: This material must be properly grounded for optimum electrical performance. See Tech Bulletin TB-2000 for mat grounding instructions.

<u>Cleaning:</u> For optimum electrical performance, surface must be cleaned regularly using an ESD mat cleaner. We suggest using our <u>Reztore Surface & Mat</u> <u>Cleaner</u>. Do not use cleaners with silicone. Silicone buildup will create an insulative film on the surface.



Micastat[®] Mat Kits - Item Numbers

Color 24" x 48"**		24" x 36"**	
Beige	<u>10350</u>	<u>10310</u>	
Blue	<u>10384</u>	<u>10344</u>	
Grey	<u>10382</u>	<u>10342</u>	

Grounding Hardware Included Special sizes available upon request. Bottom -- Double sided tape to attach.



wicastat ^o Sneet							
Micastat [®] Sheets - Item Numbers							
Size***	Beige	Blue	White	Grey			
30" x 10'	<u>10200</u>	<u>10180</u>	<u>10240</u>	<u>10290</u>			
30" x 12'	<u>10202</u>	<u>10181</u>	<u>10242</u>	<u>10291</u>			
36" x 8'	<u>10203</u>	<u>10182</u>	<u>10243</u>	<u>10292</u>			
36" x 10'	<u>10204</u>	<u>10183</u>	<u>10244</u>	<u>10293</u>			
36" x 12'	<u>10206</u>	<u>10184</u>	<u>10246</u>	<u>10294</u>			
48" x 8'	<u>10208</u>	<u>10185</u>	<u>10248</u>	<u>10295</u>			
48" x 12'	<u>10212</u>	<u>10187</u>	<u>10252</u>	<u>10297</u>			
60" x 12'	<u>10215</u>	<u>10190</u>	<u>10255</u>	<u>10300</u>			

Special sizes available upon request.

DATE:

July

2013

Grounding hardware not included. Micastat[®] Ground Kits <u>14246</u> & <u>14244</u> are recommended.

Micastat® Dissipative Laminate

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com PHONE (909) 627-8178 DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antistatic Control Products category:

Click to view products by Desco manufacturer:

Other Similar products are found below :

 13020
 13870
 13879
 13881
 13883
 13882
 14404
 2202SP
 3039
 37061
 42470
 09060
 09857
 42516
 37059
 04563
 17252
 19691

 19695
 09037
 09826
 09813
 66070
 100816
 68101
 68103
 98132
 73741
 13868
 13457
 13245
 13468
 13420
 13332
 13205
 13135

 91070
 8031
 8523
 66085
 40931
 37081
 13080
 13215
 13806
 73749
 010-0225
 17260