STATSHIELD® METAL-IN BOXED SERIES

Specifications:

Electrical Properties

Standard Document

ANSI/ESD S541 (ANSI/ESD S20.20) ANSI/ESD S11.4

Meets Requirements of:

ESD Protective Packaging Level 3 Technical Requirements

Test Procedures/Method

Surface Resistance: $1 \times 10^4 \text{ to} < 1 \times 10^{11} \text{ ohms}$ Outer Surface ANSI/ESD STM11.11 1×10^4 to $< 1 \times 10^{11}$ ohms Inner Surface ANSI/ESD STM11.11 Discharge Shielding ANSI/ESD STM11.31. EIA 541 Charge Generation Teflon: 0.09 nC/sq. in. Modified Incline Plane Quartz: 0.01 nC/sq. in. Modified Incline Plane

Typical Values


Capacitance Probe (to dissipate 1 KV) <30 volts ANSI/EIA-541/Appendix E, 1kV Discharge

Physical Properties

Film Thickness Nominal 0.0030" (0.0762mm) ±10% MIL-STD-3010, 1003 Width (Inside Dimensions) Nominal -0" / + 0.125" Length (Inside Dimensions) Nominal ± 0.125" Light Transmission >40% (Tobias) **ASTM D-1003** Heat Seal >10 lbs/in 375°F, 1/2 sec 60 psi 4600 PSI, 32 MPa Tensile Strength **ASTM 882**

Puncture Resistance >10 lbs MIL-STD-3010, 2065 Non-corrosive Pass MIL-STD-3010. M3005 Silicone Not detected FTIR

Marking Adhesion Pass IPC-TM-650 2 4 1



DescoIndustries.com Made in America

Overall Width (OW)

STATSHIELD®

Metal In Construction

Discharge Shielding RoHS

Static Shielding Bag

Opening

Length (L)



Date & Lot Code

Printed for QC

Traceablility

Low Charging Static Dissipative Proprietary Inner Polyethylene Layer

Dissipative Proprietary

Outer Polyester Layer Aluminum Shielding Layer

ANSI/ESD S541 Section 6.2 Outside an EPA

"Transportation of sensitive products outside of an EPA shall require packaging that provides:

- 1. Low charge generation
- 2. Dissipative or conductive materials for intimate contact
- 3. A structure that provides electrostatic discharge shielding."

RoHS, REACH and Conflict Minerals Statement

See the Desco Industries RoHS. REACH, and Conflict Minerals Statement: Desco.com/pdf/REACHRoHSConflictMinerals-Desco Bags.pdf

See the Desco Limited Warranty:

Desco.DescoIndustries.com/Limited-Warranty.aspx

Mixed Unsortable Plastic Scrap

Mixed unsortable plastic scrap shall contain assorted plastics of multiple grades that are co-extruded, bonded or laminated together which are unsortable into individual grades

Desco's bags are recyclable

Statshield® bags are packaged 100 per package in an oversized shielding bag. See Shielding Bag Storage at TB-7057.

Statshield® and Statfree® are Registered Trademarks of Desco Industries Inc. See Bag Selection Chart Click HERE.



United States of America

Specifications and procedures subject to change without notice.

STATSHIELD® METAL-IN BOXED, 0.0030" (0.0762mm)



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com PHONE (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407

PHONE (781) 821-8370

DRAWING NUMBER 13330

DATE: April 2018

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antistatic Control Products category:

Click to view products by Desco manufacturer:

Other Similar products are found below:

13505 13870 14404 20-053-0017 2229 2231 3039 37061 39792 42470 XON-ASB4X30 XON-ASB4X6 XON-ASB6X30 09813 09857

XON-ASB8X10 XON-ASB6X10 19695 09037 68101 68103 73741 13515 13869 13868 13485 13457 13245 13332 13205 13135 91070

8031 8523 13080 13215 157 ROLL BEIGE 1.0 VERAX1R-300R 17260 66051 12550 19863 09121 73831 13340 13338 04541 19696

16104 SPI-20686