

"If any part of the loop should open (become disconnected or have out of limit resistance), the circuit will go into the alarm state" [ref TR20.20], nonetheless, due to the redundancy inherent in the dual wire wrist strap design, the operator will continue to be grounded via the second intact wire.

Per ESD Handbook TR20.20 section 5.3.9.2.2 Dual Conductor Resistance Continuous Monitors, "This type of monitor is used with a two wire (dual conductor) wrist strap. The wrist strap assembly consists of a two-wire ground cord and a wristband that has two isolated halves. When a person is wearing the wrist strap properly, the monitor measures the loop resistance consisting of one wire of the ground cord, one-half of the wristband, the person's skin, the second half of the wristband, and a second wire in the ground cord. If any part of the loop should open (become disconnected or have out of limit resistance), the circuit will go into the alarm state.

ESD Handbook TR 20.20 paragraph 5.3.2.4.4 Test Frequency "Because wrist straps have a finite life, it is important to develop a test frequency that will guarantee integrity of the system. Typical test programs recommend that wrist straps that are used daily should be tested daily. However, if the products that are being produced are of such value that knowledge of a continuous, reliable ground is needed, and then continuous monitoring should be considered or even required"

Continuous Monitors pay for themselves improving quality, productivity, eliminating wrist strap daily testing and test result logging. Per ESD-S1.1 paragraph 6.1.3 Frequency of Functional Testing "Daily [Wrist Strap] testing may be omitted if constant monitoring is used."

Improve wrist strap contact with Reztore™ ESD Hand Lotion.

* U.S. Patents 6,052,053 and 6,205,408



Dual Wire Wrist Strap provides redundancy; even if one dual wire wrist strap conductor is severed, operator has reliable path-to-ground with other wire.

- Used with resistive loop technology continuous monitor, continuously verifies the proper resistance to ground of the operator
- · Black ABS plastic cap.
- 300 series stainless steel backplate (0.015" thick). Manufacturing date code is stamped into stainless steel back plate.
- 4mm snaps are machined to precision profile from 300 series stainless steel for a consistent and reliable connection.
- Premium metal expansion band. Inside links are constructed of 300 Series Stainless Steel. Width of links is 0.630".
- .002" polyphenylsulfone sheet is laminated to each link before assembly.
 Provides >5,000 volt RMS insulation per ASTM D149. Will not flake or peel.
- · Patented* dual wire technology
- Superior reliability. Greatly exceeds ESD S1.1 Bending Life Test. Tested at over 200,000 cycles vs. the 16,000 requirement
- Superior warranty See details of 1 year Limited Warranty at http://www.Desco.com/Warranty.aspx
- · Superior quality product Made in America at our Chino CA facility

Use patented* Dual Wire Wrist Strap with Desco Dual Wire Continuous Monitor

ITEM	REF. #	DESCRIPTION
19859	SE7500S	Premium Metal Expansion Wristband, 4mm male snaps, small, with Snap-One 6' Coil Cord, 4mm female snaps, right angle mono plug
19858	SE7500M	Premium Metal Expansion Wristband, 4mm male snaps, medium, with Snap-One 6' Coil Cord, 4mm female snaps, right angle mono plug
19857	SE7500L	Premium Metal Expansion Wristband, 4mm male snaps, large, with Snap-One 6' Coil Cord, 4mm female snaps, right angle mono plug

See Drawing 19695 for details on Snap-One Coil Cords

Premium Metal Expansion Dual Wire 4mm Wrist Straps

DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com PHONE (909) 627-8178 FAX (909) 627-7449

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370 FAX (781) 575-0172

DRAWING NUMBER 19859 DATE: March 2009

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antistatic Control Products category:

Click to view products by Desco manufacturer:

Other Similar products are found below:

13020 13490 13870 13879 13881 13883 13882 14404 2202SP 3039 37061 42470 09060 09857 42516 37059 04563 17252 19691 19695 09037 09826 09813 66070 100816 68101 68103 98132 73741 13868 13485 13457 13245 13468 13420 13332 13205 13135 91070 8031 8523 66085 40931 37081 13080 13215 13806 73749 010-0225 17260