



FEATURES

- Blue thermoplastic elastomer, copolyester construction
- Patented* latching mechanism adjusts the wristband's diameter from 1.7 to 2.6 inches
- Interior wristband resistance: < 1 x 10⁵ ohms
- Exterior wristband resistance: > 1 x 10⁷ ohms
- Unique dual contact design is to be paired with an <u>SCS MagSnap 360™ Dual-Wire Coil Cord</u> for a superior electrical connection. The magnetic connection made with the coil cord maintains a 1-5 pound perpendicular breakaway force to prevent accidental disconnects.
- Black ABS plastic cap. Molded with "MagSnap 360" trademark.
- · Backplate Material: Stainless-steel
- Compatible with <u>SCS Dual-Wire Workstation Monitors</u> and other brands that accept a 3.5 mm phono plug.
- Meets requirements of ANSI/ESD S20.20, ANSI/ESD S1.1, EN 61340-5-1 and IEC 61340-4-6
- May be cleaned with water and mild detergent or 10% isopropyl solution

Item	Description
<u>2240</u>	Wristband Only
<u>2241</u>	Wristband with 6' Coil Cord
2242	Wristband with 12' Coil Cord

Unless otherwise noted, tolerance ±10%

Specifications and procedures subject to change without notice. *U.S. Patent 6.256.847







MAGSNAP 360™ DUAL-WIRE THERMOPLASTIC WRISTBAND

SCS

920 J R INDUSTRIAL DRIVE, SANFORD, NC 27332 EAST: (919) 718-0000 | WEST: (909) 627-9634 WEBSITE: StaticControl.com DRAWING NUMBER

DATEJanuary

2018

2240

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antistatic Control Products category:

Click to view products by Desco manufacturer:

Other Similar products are found below:

13020 13490 13870 13879 13881 13883 13882 14404 2202SP 3039 37061 42470 09060 09857 42516 37059 04563 17252 19691 19695 09037 09826 09813 66070 100816 68101 68103 98132 73741 13868 13485 13457 13245 13468 13420 13332 13205 13135 91070 8031 8523 66085 40931 37081 13080 13215 13806 73749 010-0225 17260