

Retractable vacuum seal nozzle

Seal heat timer

Pneumatic jaw 1/8" heat seal

Pneumatic pressure jaw

Seal cool timer

Foot switch activated. Controls vacuum time.

The SCS Vacuum Sealer removes moisture laden air from the interior of moisture barrier bags, and heat seals the bags closed. This is part of the dry packaging process that protects surface mount devices from moisture. A vacuum sealer, a moisture barrier bag, desiccant, and humidity indicator card (HIC) are needed for dry packaging.

The SCS Vacuum Sealer is available with or without a ¼" seal bar. A retractable nozzle is used to improve bag evacuation and save bag space. The operator controls vacuum time by using the foot pedal. Timers are provided for heat sealing and cooling. By placing the heat seal jaw close to the top of the bag, the amount of bag used in the sealing process is reduced.

Specifications	Typical Value
Seal Length	20"
Seal Width	1/8"
Vacuum Pressure	< 26 Hg
Max Suction	0.8 CFM
Air Consumption	1.75 CFM
Length	25.5"
Width	10"
Height	9"
Electrical Power	120 VAC
Compressed Air	80 PSI

Item	Description
235VACUSEAL	20"
235VACUSEAL-1/4	20" with 1/4" seal bar

## 235VACUSEAL VACUUM SEALER



926 JR Industrial Drive, Sanford, NC 27332

WEB SITE: StaticControl.com PHONE (919) 718-0000 DRAWING NUMBER 235VACUSEAL

May 2016

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Bench Top Tools category:

Click to view products by Desco manufacturer:

Other Similar products are found below:

6-1372442-6 63801-4462 63801-4561 63801-7269 679527-1 691667-1 7-21000-9 768539-1 854130-1 854946-2 856203-1 904449-1 922280-9 986096-2 992438-3 1-21000-3 1-21000-1 1-25022-4 1302263353 1302263355 1302261057 1302261101 1302261206

1302261560 1302263123 1302264036 1424264-1 1424267-1 1428211-1 1428287-1 1-455755-6 1752744-1 18023-9 189763-1 1901726-1
2079747-1 21001-2 2119083-1 2119085-1 2119371-1 2161930-1 2217088-2 2217347-1 22281-9 22374-7 284565-000 F1 Handle Spring
19228-0213 2030790-2 2063796-1