




No silicone is used in the materials that make our foot grounders.
For additional information on the use and maintenance of foot grounders please ask for Tech Brief PS-2030.

Briefs PS-2057 and PS-2094.
ESD Systems.com recommends the use of 41203, 41205, 41220/41213, and 41220/41226 foot ground testers. Ask for Tech Briefs PS-2057 and PS-2094.
Operator is grounded when foot is in contact with grounded dissipative or conductive flooring.
Two heel straps are recommended for reliable grounding and ESD protection, providing ground when one foot is off the floor.

Note:



432 NORTHBORO ROAD CENTRAL
MARLBORO, MA 01752 USA
TEL. (508) 485-7390
FAX (508) 480-0257

Visit our online
library of Tech Drawings:
<http://www.esdsystems.com>

DRAWING NUMBER
TD-24104

DATE
07/05

Foot Grounder, Heel, Conductive, High Visibility, Non-Marring

Our UL listed foot grounders are rated at 250 VAC. It is not recommended to use them where exposure to line voltages above 250 VAC is possible. **Caution:** The foot grounder is for ESD control. It will not reduce or increase your risk of receiving electric shock when using or working on electrical equipment.

ITEM NO.	DESCRIPTION
24105	Heel Grounder, 2 megohm resistor, 30" tab
24104	Heel Grounder, without resistor, 30" tab

Made in America



Tab to cup resistance:

24104 - 10⁶ - 10⁷
24105 - 10⁶ - 10⁷

E. Patented* two megohm flat "flex" resistor (24105 only).

D. Adjustable snap-loc fastening system.

C. 3/4" wide, neon green elastic material stretches for comfort.

B. 3/8" wide, 30" long black polyester tab contains eight (8) electrically conductive carbon suffused fibers.

A. 0.060 inch thick non-marring, solid, three layer, rubber material. Three layers consist of a yellow dissipative outer layer with a textured grain, black conductive inner layer, and a yellow dissipative outer layer. Will not mar floors or shoes with black marks.

Components:

The High Visibility 3-Layer Non-Marring Foot Grounder features a bright yellow rubber cup and neon green snap-loc strap. The three-layer cup has a non-marring interior and exterior, and is reversible, providing extended life expectancy. This unit is suitable for cleanrooms, as there is no exposed carbon. The High Visibility Heel Grounder includes a patented* two megohm "flex" flat resistor (24105 only), 8 strand conductive tab with carbon suffused fibers, and an adjustable snap-loc fastening system. These units are UL listed. The product has been tested to ESD STM 97.2 - Floor Materials and Footwear Voltage Measurement in Combination with a Person. It is a suitable ESD footwear component in Flooring - Footwear System when used as the primary grounding method (>3.5 x 10⁷ ohms per ESD STM 97.1 Floor Materials and Footwear-Resistance Measurement in Combination with a Person.)

Description:



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Antistatic Control Products](#) category:

Click to view products by [Desco](#) manufacturer:

Other Similar products are found below :

[13505](#) [13870](#) [14404](#) [20-053-0017](#) [2229](#) [2231](#) [3039](#) [37061](#) [39792](#) [42470](#) [XON-ASB4X30](#) [XON-ASB4X6](#) [XON-ASB6X30](#) [09813](#) [09857](#)
[XON-ASB8X10](#) [XON-ASB6X10](#) [19695](#) [09037](#) [68101](#) [68103](#) [73741](#) [13515](#) [13869](#) [13868](#) [13485](#) [13457](#) [13245](#) [13332](#) [13205](#) [13135](#) [91070](#)
[8031](#) [8523](#) [13080](#) [13215](#) [157](#) [ROLL BEIGE 1.0](#) [VERAX1R-300R](#) [17260](#) [66051](#) [12550](#) [19863](#) [09121](#) [73831](#) [13340](#) [13338](#) [04541](#) [19696](#)
[16104](#) [SPI-20686](#)