

Features

- Basic Protektive Pak tray
- Great container for Kanban
- Permanently static dissipative foam (shuntable) laminated to our impreganted corrugated material provides ESD and shock protection

Foam Electrical Properties: 1 x 10⁴ to < 1 x 10¹¹ ohms

Foam Thickness: 1/4" (+/- 1/16" tolerances)

ltem	Size I.D L x W x D (IN)
37650	17-3/4 x 10-3/4 x 2-1/8
37651	17-7/8 x 13-5/8 x 2-1/8
37653	19-1/4 x 13-1/8 x 2-1/8
37654	19-3/8 x 15-3/4 x 2-1/8
37652	24 x 13-1/2 x 2-1/8

Dimensional tolerances are +/- 1/8" unless otherwise specifed

Meets the required limits of ANSI/ESD S20.20, Packaging standard ANSI/ESD S541, and worksurface standard ANSI/ESD S4.1

SPECIFICATIONS

Properties Surface Resistance Sloughing Test

Typical Values

1 x 10^6 to < 1 x 10^9 ohms Negligible surface damage at 10 cycles and <5% of surface damage at 200 cycles in Taber Abrasion Test. No conductive particles abrased from surface Complete recyclability of package

Test Procedures/Method

ANSI/ESD STM11.11 ASTM D4060 at 70 rpm with CS-17 abrasive-coated wheels and 1000 grams load Rockwell International Test Report of January 8, 1992 Rockwell International Test Report of January 8, 1992

Recyclability



© 2018 DESCO INDUSTRIES INC Employee Owned

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antistatic Control Products category:

Click to view products by Desco manufacturer:

Other Similar products are found below :

 13020
 13870
 13879
 13881
 13883
 13882
 14404
 2202SP
 3039
 37061
 42470
 09060
 09857
 42516
 37059
 04563
 17252
 19691

 19695
 09037
 09826
 09813
 66070
 100816
 68101
 68103
 98132
 73741
 13868
 13457
 13245
 13468
 13420
 13332
 13205
 13135

 91070
 8031
 8523
 66085
 40931
 37081
 13080
 13215
 13806
 73749
 010-0225
 17260