



47200 in use (<u>47204</u> Ground cord sold separately)



47201 in use





Made in the United States of America

SPECIFICATIONS

- Ideal for working on heavier assemblies in an EPA
- ESD protective for use with ESD sensitive assemblies
- Durable 1/4" (6mm) thick Dissipative, Crosslink Polyethylene Foam
- Galvanized Steel Turntable located at the bottom
- Size: Choice of 12-1/2" (318mm) or 15-1/2" (394mm) Octagon (across flats)
- Very low profile both sizes only 1" (25mm) high
- Weight capacity 50 lbs (23 Kg)
- Volume Resistance 1 x 10⁶ to < 1 x 10⁹ ohms per ANSI/STM11.12
- Meets worksurface require limit of ANSI/ESD S20.20 per ANSI/ESD S541 and ESD TR53
- Electrostatic charges removed to ground via contact on grounded ESD worksurface or via ground cord from ring terminal
- Made in the United States of America

Item	Size (Octagon across flats)
<u>47200</u>	12-1/2" (318mm)
<u>47201</u>	15-1/2" (394mm)



Galvanized Steel Turntable

Unless specified tolerance is ±10%

Specifications and procedures subject to change without notice.

ESD DISSIPATIVE TURNTABLE

PROTEKTIVE PAK

PROTEKTIVE PAK

13520 MONTE VISTA AVENUE, CHINO, CA 91710 PHONE (909) 627-2578

ProtektivePak.com

DRAWING NUMBER 47200 June 2016

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Storage Boxes & Cases category:

Click to view products by Desco manufacturer:

Other Similar products are found below:

120Y 120R DB613 18090-2 A221 17800-2 T221 T600 T824 57/13512PK 6777TF T1400 3005C A101 DB226 DB216 T4004 T623
T9100 T5008 DB211 K818 A208 A618 6734PF T9501 18192-2 DB201 6785TC T900BK A602 A209 5202CL T1408B PPK-29087
SE52F, RD 38845 38848 38851 38854 K216 54439 54445 54448 54451 55600 1206706 3069520 3203008 5020658