



Part No.	Box Size - L x W x D
<u>57020</u>	2.56" x 3.5" x 1.75"
<u>57021</u>	7.0" x 3.5" x 1.0"
<u>57022</u>	7.0" x 5.0" x 0.5"

Features

- Conductive Velostat® hinged container
- · Ideal for storage, kitting, and in-process handling of static-sensitive assemblies and devices
- Made from Velostat® injection-molded, conductive polypropylene
- · Containers are noncorrosive and lightweight
- · Molded pin hinge provides better security and reliability than snap hinges

SPECIFICATIONS

Physical Properties		
Property	Test Method	Value
Hardness	ASTM D2240	67-71 Shore D
Maximum Temp. Exposure		180°F
Tensile Strength	ASTM D638	2800 - 3000 psi
Flex Modulus	ASTM D790	130,00 - 150,000 psi
Electrical Properties		
Volume Conductive	ASTM D991	<500 ohms/cm
Volume Resistance	ANSI/ESD STM11.12	<1 x 10 ⁴ ohms

Chemical Resistance	Reactions	
Alcohol	Resistant	
Aromatic Hydrocarbons	Severe Attack	
Aliphatic Hydrocarbons	Moderate Attack	
Concentrated Acids	Slight Attack	
Concentrated Alkalines	Slight Attack	
Kerosene	Severe Attack	
Ketones (Acetone)	Moderate Attack	
Mineral Oil	Slight Attack	
Oil & Gasoline	Moderate Attack	



Specifications and procedures subject to change without notice

CONDUCTIVE VELOSTAT® HINGED CONTAINER

PROTEKTIVE PAK

PROTEKTIVE PAK

13520 MONTE VISTA AVENUE, CHINO, CA 91710 PHONE (909) 627-2578 ProtektivePak.com

DRAWING NUMBER 57020

DATE: July 2018

Unless otherwise noted, tolerance is ±10%

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antistatic Control Products category:

Click to view products by Desco manufacturer:

Other Similar products are found below:

13020 13490 13870 13879 13881 13883 13882 14404 2202SP 3039 37061 42470 09060 09857 42516 37059 04563 17252 19691 19695 09037 09826 09813 66070 100816 68101 68103 98132 73741 13868 13485 13457 13245 13468 13420 13332 13205 13135 91070 8031 8523 66085 40931 37081 13080 13215 13806 73749 010-0225 17260