

#### Disclaimer:

All statements, technical data, and recommendations contained herein are based upon tests we believe to be reliable. However, the accuracy or completeness thereof is not guaranteed. The proper and correct applications of products and data is the responsibility of the user. Statements or recommendations not contained herein shall have no force or effect unless embodied in a written agreement signed by authorized officers of DESCO INDUSTRIES INC.

\*Rubber material is vulcanized and may contain sulfur

## RoHS 2, REACH, and Conflict Minerals Statement

None of the RoHS 2 restricted materials, or REACH substances of very high concern as of 2015/06/15, or Conflict Minerals are intentionally added in manufacturing this product. Ref: European Union Directive 2011/65/EU and Regulation (EC) No. 1907/2006/CE. See Desco Limited Warranty at Desco.com.

#### **Limited Lifetime Warranty:**

Desco warrants for one year that Statfree® matting products will be free of defects in materials and workmanship and will guarantee dissipative/conductive mat properties for the life of the mat. Damage to matting caused by misuse of any kind, including using inappropriate cleaners is not covered by Desco Limited Warranty.

Specifications and procedures subject to change without notice.

## STATFREE® UC2 DISSIPATIVE DUAL LAYER ULTRA CLEAN RUBBER



## **Electrical Properties:**

Property Test Method Value

Rtt Resistance (Blue top layer): ANSI/ESD S4.1 1 x  $10^6$  to < 1 x  $10^9$  ohms

Rtt Resistance (Black bottom layer): ANSI/ESD S4.1 < 1 x 10<sup>5</sup> ohms

## **Specifications:**

Construction: Dual-layer Rubber¹
Thickness: 0.080" (2mm)
Texture:² Slight Emboss

Colors:<sup>2</sup> Blue

<sup>1</sup>Rubber material is vulcanized and may contain sulfur.

<sup>2</sup>Color and texture may vary between lots and mils

No Detectable Levels of Silicone or DOP: Approved\* for used in Class 100 cleanrooms. Request a sample to test to your requirements.

**Grounding:** This material must be properly grounded for optimum electrical performance. See Tech Bulletin <u>TB-2000</u> for mat grounding instructions.

<u>Cleaning:</u> For optimum electrical performance, surface must be cleaned regularly using an ESD mat cleaner. We suggest using our <u>Reztore Surface & Mat Cleaner</u>. Do not use cleaners with silicone. Silicone buildup will create an insulative film on the surface.

#### **Compatible with Workstation Continuous Monitors**

#### 

Item	Size**		Ite
66320	30" x 40'		66
66321	16" x 24"		66
66322	24" x 36"		66
<u>66323</u>	24" x 48"		66
66324	30" x 60"		66
<u>66325</u>	30" x 72"		

Item <sup>†</sup>	Size**
<u>66326</u>	16" x 24"
66327	24" x 36"
<u>66328</u>	24" x 48"
<u>66329</u>	30" x 60"
<u>66330</u>	30" x 72"

<sup>†</sup> Cleaned and Packaged in a Class 1000 Controlled Environment. Click HERE to learn more.

#### Mat Top Kit Includes

- 1 Mat, size as specified
- 1 14213 Grounding Kit
- 1 Sample (4oz) of Reztore Mat Cleaner

### \*\*Tolerances:

Width ± .0250"

Length ± .0250" every 1 linear foot of running material. Thickness ±10%

STATFREE® UC DISSIPATIVE DUAL LAYER ULTRA CLEAN RUBBER

Matting materials have a tendency to shrink slightly when first unrolled. In applications where length is critical, allow the material to relax for at least 4 hours before cutting to size. Using care, always trim with a sharp knife or razor blade.



## PERSON MEST ASSAULABILIT AVE. CUINIO CA CATAO, MEDICITE D

**DESCO WEST:** 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: <u>Desco.com</u> PHONE (909) 627-8178

**DESCO EAST:** ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370

STATFREE® UC2
DRAWING PM-131

DATE: March 2021



<sup>\*</sup> Although cleanroom requirements vary, Statfree<sup>®</sup> UC2 material will most likely meet the requirements for a class 100 or higher clean room.

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antistatic Control Products category:

Click to view products by Desco manufacturer:

Other Similar products are found below:

14404 2202SP 37061 42470 09813 09857 09037 09086 09813 68101 68103 98132 73741 13457 13245 13420 13205 91070 66085

13080 010-0115 13390 09121 07501 09204 66086 66121 16316 13331 ZJ-SD100 1900-8X12 1910-10X12 82A3 1900-6X8 1900-7-15

19866 20-082-1012 STS1327 STW404111 20-871-1418 20-871-1624 20-871-1818 20-871-1824 20-872-1418 53707 ELSEC 5/10 52889

52867 52865 52849