



**Grey**

**Grounding & Cleaning**

If the material is used on top of an already properly grounded surface, [grounding hardware](#) may not be necessary. Where no properly grounded surface is available, [grounding hardware](#) is required to provide a path-to-ground. Rtg compliance verification measurements must be made as outlined in ESD TR53 with a [surface resistance meter](#).

See Tech Bulletin [TB-7000](#) for Reztore® Surface & Mat Cleaner Application Instructions.

**RoHS 3, REACH, and Conflict Minerals Statement**

See the Desco Industries RoHS 3, REACH, and Conflict Minerals Statement: [Descoindustries.com/ROHS.aspx](#)

See the Desco Limited Warranty: [Desco.Descoindustries.com/Limited-Warranty.aspx](#)

See the Desco Disclaimer: [Desco.Descoindustries.com/Disclaimer.aspx](#)

**Statfree S Plus™ Dissipative Homogeneous Vinyl**

**Specifications**

**Standard Document**  
ANSI/ESD S20.20

**Meets Requirements of:**  
Flooring

**Electrical Properties**  
Rtt Resistance:  
Rtg Resistance:

**Typical Values**  
< 1 x 10<sup>9</sup> ohms  
< 1 x 10<sup>9</sup> ohms

**Test Procedures/Method**  
ANSI/ESD STM7.1 and ESD TR53  
ANSI/ESD STM7.1 and ESD TR53

**Physical Properties**

**Construction:**  
**Thickness:**  
**Color:\*\***  
**Texture:\*\***  
**Weight:**

Vinyl/Nitrile Floor Runner  
0.375"  
Grey  
Non-directional, heavy embossed, soil and abrasion resistant  
0.65 lbs/ft<sup>2</sup> (0.317g/cm<sup>2</sup>)

**Tolerances:**

Width +/- 0.250"  
Length +/- 0.250" every 1 linear foot of running material.

Matting materials have a tendency to shrink slightly when first unrolled. In applications where length is critical, allow the material to relax for at least 4 hours before cutting to size. Always trim with a sharp knife or razor blade.

\*\*Color and texture may vary between lots and mills

For Sizes and Item Numbers, [Click Here](#)



Made in the United States of America

Specifications and procedures subject to change without notice

**STATFREE S PLUS™ FLOOR MAT, VINYL, HOMOGENEOUS, ANTI-FATIGUE, .375" (9.5MM)**



DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: [Desco.com](#)  
PHONE (909) 627-8178 FAX (909) 627-7449

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407  
PHONE (781) 821-8370 FAX (781) 575-0172

MATERIAL  
STATFREE S Plus  
DRAWING PM-120

DATE:  
February  
2019

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Antistatic Control Products](#) category:*

*Click to view products by [Desco](#) manufacturer:*

Other Similar products are found below :

[13020](#) [13490](#) [13870](#) [13879](#) [13881](#) [13883](#) [13882](#) [14404](#) [2202SP](#) [3039](#) [37061](#) [42470](#) [09060](#) [09857](#) [42516](#) [37059](#) [04563](#) [17252](#) [19691](#)  
[19695](#) [09037](#) [09826](#) [09813](#) [66070](#) [100816](#) [68101](#) [68103](#) [98132](#) [73741](#) [13868](#) [13485](#) [13457](#) [13245](#) [13468](#) [13420](#) [13332](#) [13205](#) [13135](#)  
[91070](#) [8031](#) [8523](#) [66085](#) [40931](#) [37081](#) [13080](#) [13215](#) [13806](#) [73749](#) [010-0225](#) [17260](#)