

Item	Description	Circumference		
		Minimum	Maximum	Width
<u>09200</u>	Wristband only, Red, White and Blue	5.75 in.	13 in.	0.630"
<u>09041</u>	Wristband only, Black	5.75 in	13 in.	0.630"
<u>09220</u>	Wristband only, White	5.75 in.	13 in.	0.630"
* <u>09230</u>	Wristband only, White	5.75 in.	13 in.	0.630"
<u>09042</u>	Wristband only, X-large, Black	6.25 in.	14.5 in.	0.630"
<u>09085</u>	Wrist Strap, Black, 6' coil cord	5.75 in.	13 in.	0.630"
<u>91070</u>	Wrist Strap, Black, 6' cord & angle banana	5.75 in.	13 in.	0.630"
<u>09221</u>	Wrist Strap, White, 6' coil cord	5.75 in.	13 in.	0.630"
* <u>09231</u>	Wrist Strap, White, 6' coil cord	5.75 in.	13 in.	0.630"
<u>09222</u>	Wrist Strap, White, 10' coil cord	5.75 in.	13 in.	0.630"
* <u>09232</u>	Wrist Strap, White, 10' coil cord	5.75 in.	13 in.	0.630"

*Cleaned and Packaged in a Class 1000 Controlled Environment. Click HERE for details.

Meets ANSI/ESD S1.1 wristband resistance interior < 100 kilohms (<1 x 10⁵ ohms) Meets ANSI/ESD S1.1 wristband resistance exterior >10 megohms (>1 x 10⁷ ohms) Meets ANSI/ESD S20.20 and Wrist Strap standard ANSI/ESD S.1

- A. ABS cap with slotted opening to allow size adjustment.
- B. 300 Series Stainless Steel Backplate forms channel to hold up to 10 links of band allowing size adjustment.
- C. 4mm snap stud machined from 300 series stainless steel. Fits to 4mm spring loaded medical type socket. Coil cord disengages from snap with 1-5 lbs. of perpendicular force.
- D. Inside links constructed of 300 Series Stainless Steel. Width of links is 0.630".
- E. .002" polyphenylsulfone sheet is laminated to each link. Provides >5,000 volt RMS insulation per ASTM D149. Scratch resistant.
- F. Size is adjusted by sliding 1 to 10 links of the band into the backplate "C" channel.
- G. 300 Series Stainless Steel clip for electrical contact between snap stud and backplate.
- H. Underwriters Laboratory listing 90P1C.



Unless otherwise noted, tolerance ± 10% Specifications and procedures subject to change without notice.	Premium Metal Expansion Wristband			
DESCO	DESCO WEST: 3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com PHONE (909) 627-8178 FAX (909) 627-7449 DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370 FAX (781) 575-0172	DRAWING NUMBER 09041	DATE: January 2016	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antistatic Control Products category:

Click to view products by Desco manufacturer:

Other Similar products are found below :

 13505
 13870
 14404
 20-053-0017
 2229
 2231
 3039
 37061
 39792
 42470
 XON-ASB4X30
 XON-ASB6X30
 09813
 09857

 XON-ASB8X10
 XON-ASB6X10
 19695
 09037
 68101
 68103
 73741
 13515
 13869
 13868
 13457
 13245
 13332
 13205
 13135
 91070

 8031
 8523
 13080
 13215
 157 ROLL BEIGE 1.0
 VERAX1R-300R
 17260
 66051
 12550
 19863
 09121
 73831
 13340
 13338
 04541
 19696

 16104
 SPI-20686
 66051
 12550
 19863
 09121
 73831
 13340
 13338
 04541
 19696