

The re-positionable configuration of the Heel Grounder extends the life of the product and the elastic loop provides a secure and comfortable fit. This quality Heel Grounder features a durable three-layer sole and a 24 inch conductive ribbon. 1 or 2 Megohm Resistor. Lot coded for QC traceability. Heel grounders are UL listed.

Properties	Typical Value	Test Method
Elastic Hook and Loop	3/4"	
Elastic Strap	Black	
Sole Interior	Non-marking	
Sole Exterior	<1x 10 ⁶ ohms	
Total Grounder	<1.2 x 10 ⁶ ohms	ESD-SP9.2, ESD TR53

Item	Description
HGC1M	Cup Style Heel Grounder, 1 Megohm Resistor
HGC2M	Cup Style Heel Grounder, 2 Megohm Resistor

UL Listed


Note: This product is not recommended for use on equipment with operating voltage exceeding 250 VAC.

CAUTION: The ESD Series is for electrostatic control. It will not reduce or increase your risk of receiving electric shock when using or working on electrical equipment. Follow the same precautions you would use without wrist straps, including:

- Make certain that equipment having a grounding type plug is properly grounded.
- Make certain that you are not in contact with grounded objects other than through the ESD Series

HGC1M CUP STYLE HEEL GROUNDER		_
926 JR Industrial Drive, Sanford, NC 27332	DRAWING	DATE
WEB SITE: <u>StaticControl.com</u>	NUMBER	October
PHONE (919) 718-0000	HGC1M	2015

Elastic Hook and Loop Strap for Comfort and Visibility



Wider Sole for Larger Contact Surface

Unless otherwise noted, tolerance ± 10%

Specifications and procedures subject to change without notice.





X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antistatic Control Products category:

Click to view products by Desco manufacturer:

Other Similar products are found below :

 13020
 13870
 13879
 13881
 13883
 13882
 14404
 2202SP
 3039
 37061
 42470
 09060
 09857
 42516
 37059
 04563
 17252
 19691

 19695
 09037
 09826
 09813
 66070
 100816
 68101
 68103
 98132
 73741
 13868
 13457
 13245
 13468
 13420
 13332
 13205
 13135

 91070
 8031
 8523
 66085
 40931
 37081
 13080
 13215
 13806
 73749
 010-0225
 17260