

The HGS1MD-RED heel grounder features a D-Ring Strap and elastic hook and loop for adjustability. Compliance verification is simplified by the bright red elastic strap. Heel Grounders are designed and manufactured for comfort, durability and cost effectiveness.

Properties	Typical Value	Test Method
Hook and Loop	3/4"	
Elastic Strap	Red	
Sole Interior	Non-marking	
Sole Exterior	<10⁵ ohms	
Total Grounder	1.0 x 10 ⁶ ohms	ANSI/ESD S20.20, EIA 625 ESD-SP9.2

li	tem	Description
F	HGS1MD-RED	Red Standard Heel Grounder, 1 Megohm Resistor

Note: This product is not recommended for use on equipment with operating voltage exceeding 250 VAC.

CAUTION: The ESD Series is for electrostatic control. It will not reduce or increase your risk of receiving electric shock when using or working on electrical equipment. Follow the same precautions you would use without wrist straps, including:

Make certain that equipment having a grounding type plug is properly grounded.
Make certain that you are not in contact with grounded objects other than through the ESD Series.

Unless otherwise noted, tolerance ± 10% Specifications and procedures subject to change without notice.	HGS1MD-RED - STANDARD HEEL GROUNDER, D-RING, RED ELASTIC		
SCS	926 JR Industrial Drive, Sanford, NC 27332	DRAWING	DATE
	WEB SITE: <u>StaticControl.com</u>	NUMBER	August
	PHONE (919) 718-0000	HGS1MD-RED	2015

24" Conductive Ribbon

© 2015 DESCO INDUSTRIES INC. Employee Owned

D-Ring for Adjustability

Red Elastic Strap

for High Visibility

2-Layer Rubber Sole

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Antistatic Control Products category:

Click to view products by Desco manufacturer:

Other Similar products are found below :

 13020
 13870
 13879
 13881
 13883
 13882
 14404
 2202SP
 3039
 37061
 42470
 09060
 09857
 42516
 37059
 04563
 17252
 19691

 19695
 09037
 09826
 09813
 66070
 100816
 68101
 68103
 98132
 73741
 13868
 13457
 13245
 13468
 13420
 13332
 13205
 13135

 91070
 8031
 8523
 66085
 40931
 37081
 13080
 13215
 13806
 73749
 010-0225
 17260