



# Dual Conductor Ground Cord 2300 Series



The 3M™ Dual Conductor Ground Cord is part of a personnel ground monitoring system. The 3M™ Workstation Monitor product line (Models 724, 725, and 790) uses a dual conductor type wrist strap system consisting of a dual conductor wristband and ground cord. The dual system allows for a monitored loop resistance measurement, which includes the wristband contact to the wearer and a redundant grounding path. If one conductor of the system fails, the other can still function maintaining the grounding of the person. As a result, this prevents static from being generated by the person, eliminating possible damage to static-sensitive electronic components. The series includes cords available in 5, 10, or 20 feet lengths and are compatible with all existing 3M dual conductor fabric, metal, and thermoplastic wristbands.

3M™ Dual Conductor Cord 2300 Series features a new cord construction with a double insulated jacket which improves the cord's durability to repeated flexing and provides for a lighter weight cord. In addition, the "positive" plug grip makes it easy to insert and remove the cord from a remote input jack. The 3M™ Dual Conductor Ground Cords 2360, 2370, and 2371 are a straight plug design.

Two new series of right angle plug connection designs have been added. The 3M™ Dual Conductor Ground Cords 2360R, 2370R, and 2371R, which use a 3.0 mm diameter plug tip, are recommended for use with 3M monitors and some other monitor manufacturers that use a smaller input jack design. The 2360R, 2370R, and 2371R ground cords are identified by gray overmolded ends.

The 3M™ Dual Conductor Ground Cords 2391, 2392, and 2393, which use a 3.4 mm diameter plug tip, are recommended for use with other manufacturers' monitors that use a larger input jack design. The 2391, 2392, and 2393 ground cords are identified by blue overmolded ends.

Feature (Typical Value)	3M™ Dual Conductor Ground Cords 2300 Series								
Model Number	2360	2360R	2370	2370R	2371	2371R	2391	2392	2393
<b>Usable Working Length</b> P = Practical E = Extended									
P 5 ft. E 7 ft.	x	x					x		
P 10 ft. E 12 ft.			x	x				x	
P 20 ft. E 24 ft.					x	x			x
<b>Cord Design</b> Double Insulated Jacket									
External: Hytrel Internal: Polypropylene	x	x	x	x	x	x	x	x	x
Color	Gray	Gray	Gray	Gray	Gray	Gray	Gray	Gray	Gray
<b>Overmolded Ends Design</b>									
Hytrel	x	x	x	x	x	x	x	x	x
Color	Gray	Gray	Gray	Gray	Gray	Gray	Blue	Blue	Blue
<b>Plug End Type</b>									
Straight	x		x		x				
Right Angle		x		x		x	x	x	x
<b>Plug Contact</b>									
Tip: Stainless Steel Barrel: Ni Plated Phos/Bronze	x	x	x	x	x	x	x	x	x
<b>Plug Tip Diameter</b> (Remote Plug End)									
3.0 mm (+/-0.08 mm)	x	x	x	x	x	x			
3.4 mm (+/- 0.08 mm)							x	x	x
<b>Plug Barrel Diameter</b>									
0.135 in. (+/-0.003 in.)	x	x	x	x	x	x	x	x	x
<b>Flex Life</b> (3M Test Method)									
Number of Flexes (>100,000)	x	x	x	x	x	x	x	x	x
<b>Electrical Resistance</b> (End to End)									
Tip to Tip / Barrel to Barrel 1 Megohm (+/-10%)	x	x	x	x	x	x	x	x	x
<b>Ground Cord Compatibility</b> (With Dual Conductor Wrist Strap Monitors)									
3M	x	x	x	x	x	x			
Credence Technologies	x	x	x	x	x	x			
Novx Corporation							x	x	x
Semtronics							x	x	x

3M is a trademark of 3M Company.

**Important Notice**

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.



**Electronic Solutions Division**

6801 River Place Blvd.  
Austin, TX 78726-9000  
www.3M.com/electronics

**Warranty; Limited Remedy; Limited Liability.**

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



Recycled paper  
40% Pre-consumer waste paper  
10% Post-consumer waste paper

Litho in USA  
© 3M 2006 98-0799-0777-4-A

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Desco manufacturer](#):*

Other Similar products are found below :

[8810](#) [CTM051](#) [66168](#) [66169](#) [66210](#) [700630](#) [13490](#) [13879](#) [13881](#) [14000](#) [15058](#) [2234](#) [2370](#) [980E](#) [1/6PLDES1200](#) [2121211](#) [HGS1MD-RED](#) [35596](#) [35630](#) [35874](#) [42541](#) [35996](#) [35999](#) [09200](#) [42516](#) [42500](#) [24723](#) [49111](#) [06742](#) [81270](#) [07502](#) [09214](#) [1001230](#) [10439](#) [10566](#)  
[14240](#) [14213](#) [73614](#) [13762](#) [13205](#) [770000](#) [66085](#) [66075](#) [40981](#) [40980](#) [40931](#) [37750](#) [34454](#) [13806](#) [66106](#)