

Modern Motion...

Miga Analog Driver, V5 Technical Notes

Released: November 6, 2008

The Miga Analog Driver V5 (MAD-V5) is a simple MOSFET switch designed to safely power the MigaOneTM actuators across a wide range of speeds or input voltages.

The MAD-V5 allows either push-button operation, or external GATE (CNTL) signals to actuate the MigaOne until the END limit is reached (goes LOW). The MAD-V5 then cuts power momentarily, preventing overheating of the SMA wires. The Gate transistor allows up to 30V input, but it is recommended to use logic (2.5 to 5-Volt) levels. Pulse-Width-Modulated (PWM) signals can be applied at the Gate to control the actuation speed for a set voltage. For instance, the application of +28VDC power to the MigaOne would result in very fast actuation (~70ms). But with a PWM signal with a 50% duty cycle [Ton/(Ton+Toff)], the actuation speed would be significantly reduced: offering simple PWM speed control of the MigaOne actuators.



Miga Analog Driver V5 -Pinout Diagram

JP1: Your power supply and/or micro-controller JP2: MigaOne actuator, 3-Pin Molex connector (note V+ location for polarity) Note: Maximum peak current: 7A, maximum continuous current: 5A. Refer to the *MigaOne Application Notes* for more details.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DFRobot Accessories category:

Click to view products by DF Robot manufacturer:

Other Similar products are found below :

 FIT0514
 FIT0261
 DFR0300
 DFR0017
 DFR0029-B
 DFR0029-W
 DFR0031-B
 DFR0251
 DFR0332
 DFR0411
 DFR0430

 FIT0490
 FIT0491
 SEN0038
 SEN0156
 DFR0008
 DFR0012
 DFR0016
 DFR0019
 DFR0021-G
 DFR0055
 DFR0060
 DFR0063
 DFR0074

 DFR0117
 DFR0171
 DFR0224
 DFR0256
 DFR0258
 DFR0259
 DFR0274
 DFR0308
 DFR0310
 DFR0382
 DFR0457

 FIT0003
 FIT0005
 FIT0016
 FIT0033
 FIT0038
 FIT0039
 FIT0040
 FIT0085
 FIT0101
 FIT0160