

KIT0200

KIT0200 includes the following products

- DFR1146 LattePanda Mu (N100,8GB RAM,64GB eMMC)
- FIT0981 LattePanda Mu Active Cooler
- DFR1142 Lite Carrier for LattePanda Mu

DFR1146 LattePanda Mu (N100,8GB RAM,64GB eMMC)

CPU

- Intel® Processor N100
 - Cores: 4
 - Max Turbo: 3.4GHz
 - Cache: 6MB
 - TDP: 6~35W configurable

Memory

- LPDDR5 8GB
 - Speed: 4800MT/s
 - ECC: Support IB ECC

Storage

- eMMC 5.1 64GB
 - Speed: HS400

BIOS

- AMI UEFI 128Mbit SPI BIOS

Graphs

- Intel® UHD Graphics
 - EU: 24
 - Max Turbo: 750MHz
 - 3D Acceleration: DirectX 12.1; OpenGL 4.6; Vulkan 1.2

Display

- eDP 40Pin Connector
 - Support: eDP 1.4b
 - Max Resolution: 4096 x 2160 @ 60Hz
- Digital Display Interface

- Support: DisplayPort 1.4; HDMI 2.0
- Max Resolution: 4096 x 2160 @ 60Hz
- Max Outputs: 3

I/O

- PCIe 3.0: up to 9 lanes
- SATA 3.0: up to 2 ports
- USB 3.2 (10Gbps): up to 4 ports
- USB 2.0 (480Mbps): 8 ports
- Audio: HD Audio; I2S
- Camera: MIPI CSI-2, up to 8 lanes
- SPI: Yes, for second BIOS ROM and discrete TPM
- SMBus: Yes
- I2C: SoC 4 Ports
- UART: SIO 1 Port; SoC 3 Ports
- GPIO: up to 64 pins expanded by shift registers

Power

- Supply Voltage:
 - VIN: 9~20V
 - RTC Battery: 3V

Operating System

- Official Support:
 - Windows 10 Enterprise LTSC
 - Windows 11
 - Ubuntu 22.04 LTS

Environment

- Operating Temperature: 0~60°C
- Operating Humidity: 0~80% relative humidity, non-condensing

Dimensions

- 69.6 x 60mm

FIT0981 LattePanda Mu Active Cooler

- Compatible motherboard: LattePanda Mu
- Operating voltage: 5V
- Operating current: 0.35A
- Maximum rotational speed: 4000 RPM
- Wire length: 105mm
- Interface type: PH2.0-4P
- Dimensions: 69.6 * 50.4 * 19mm

- Material: Aluminum alloy
- Weight: 69g

DFR1142 Lite Carrier for LattePanda Mu

Power Input

- USB Type-C: 15V (Max 3A)
- DC 5.5x2.5mm: 12~20V (Max 10A)

Internal Interfaces

- PCIe 3.0 x4 slot (only available when using 12V power supply)
- M.2 M Key 2230 (PCIe 3.0 x1)
- M.2 E Key 2230 (PCIe 3.0 x1, USB2.0)
- RTC battery socket (CR1220 3V)
- CPU fan socket
- Gravity-4P UART
- Gravity-4P I2C

External Interfaces

- USB 3.2 10Gbps x2
- Gigabit Ethernet
- USB 2.0 x2
- HDMI 2.0

Dimensions

3.5 inches, 146mm×102mm

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Development Boards & Kits - Other Processors](#) category:

Click to view products by [DF Robot](#) manufacturer:

Other Similar products are found below :

[KIT_AURIX_TC233LP_TRB](#) [STM8S/32-D/RAIS](#) [QB-R5F110PJ-TB](#) [ST7MDT1-EMU2](#) [KITA2GTC3975VTRBSTOBO1](#)
[RTK5572TKCS00000BE](#) [ST623X-KIT/220](#) [STEVAL-ISV014V1](#) [KIT_XC836_EK_V1](#) [XIAO STARTER KIT](#) [SIBRAIN FOR](#)
[AVR128DA64](#) [CLICKER 4 FOR TMPM3H](#) [ACRYLIC CASE FOR XIAO EXPANSION BOARD](#) [RSSDEMO50F-AA-13# DEMO KIT](#) [VS](#)
[1000 DEMO BOARD](#) [SIBRAIN FOR AVR64DA64](#) [XIAO RP2040](#) [GSM CLICK](#) [CODEGRIP ADAPT V6](#) [DUAL SMART USB CHARGER](#)
[WIZFI360-EVB-PICO](#) [EDGE CONTROL ENCLOSURE KIT](#) [DK-SOC-10AS066S-E](#) [902-0183-000](#) [Y-ASK-RL78F13-V2](#) [Y-ASK-](#)
[RL78F14-V2](#) [Y-ASK-RL78F15-V2](#) [KITA2GTC3895VTRBTOBO1](#) [KITA2GTC3995VTRBTOBO1](#) [CONNECTEVE](#) [R0K521380S000BE](#)
[R0K578L1CD000BR](#) [LV-24-33 V6 44-PIN TQFP MCU CARD EMPTY](#) [LV-24-33 V6 64-PIN TQFP MCU CARD EMPTY](#) [LV-24-33 V6 80-](#)
[PIN TQFP 1 MCU CARD EMPTY](#) [32X32 RGB LED MATRIX PANEL - 6MM PITCH](#) [READY FOR XMEGA CASING \(WHITE\)](#) [RELAY4](#)
[BOARD](#) [ETHERNET CONNECTOR](#) [RFID CARD 125KHZ - TAG](#) [RFM12B-DEMO](#) [MAROON](#) [MAX232](#) [MAX3232 BOARD](#) [THREE-](#)
[AXIS ACCELEROMETER BOARD](#) [TINKERKIT HALL SENSOR](#) [TOUCHPANEL CONTROLLER](#) [MIKROBOARD FOR AVR WITH](#)
[ATMEGA128](#) [MIKROBUS CAPE](#) [MIKROETH 100 BOARD](#)