
5mm Discrete LED **High Efficiency** Diffused



521-9246, -9248, -9250, -9704



PART NO.	<u>COLOR</u>		
521-9246	Red		
521-9248	Yellow		
521-9250	Green		
521-9704	Orange		

MOUNTING CLIP: 515-0004 located on page 6-48

ABSOLUTE MAXIMUM RATINGS $(T_A=25^{\circ}C)$	Red -9246	Yellow -9248	Green -9250	Orange -9704	
Power Dissipation (mW) Derating (mW/°C) From 25°C 1. (mA/°C) From 50°C	135 1.8	85 1.6	135 1.8	135 .5¹	
Forward Current (mA)	25	20	25	30	
Peak Current (mA) Pulse width = 10µs	500	500	500	500	
Operating Temperature (°C)	-55/+100	-55/+100	-20/+100	-55/+100	
Storage Temperature (°C)	-55/+100	-55/+100	-55/+100	-55/+100	
Soldering Temperature	260°C, 5 seconds, 1.6 mm from case				

Solder Adherence per MIL-STD-202E, Method 208C

OPERATING CHARACTERISTICS (T	Γ _A =25°C)	Red -9246	Yellow -9248	Green -9250	Orange -9704
Luminous Intensity (mcd) I _F =10mA	Min. Typical	4 7	4 8	4.2 5.2	4 7
Peak Wavelength (nm) λ Peak	Typical	635	583	565	600
Viewing Angle (2Θ ½)	Typical	60°	60°	60°	60°
Forward Voltage (V) I _F =10mA	Typical Max.	2.2 3	2.2 3	2.3 3	1.9 2.4
Reverse Voltage (V), I _R =100μA	Min.	5	5	5	5

 $[\]Theta^{\,\,|}$ is the off axis angle at which the luminous intensity is half the axial luminous intensity

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Standard LEDs - Through Hole category:

Click to view products by Dialight manufacturer:

Other Similar products are found below:

LTL-10254W LTL-1214A LTL-2231AT LTL-3251A LTL-4262N LTL-433P LTL-5234 LTL87HTBK LTW-87HD4B HLMP-EL30-PS0DD 1L0532V23G0TD001 NSPW500CS LD CQDP-1U3U-W5-1-K LP379PPG1C0G0300001 SLR-342MC3F SLX-LX3044GD SLX-LX3044ID SLX-LX3044YD 1.90690.3330000 SSS-LX4673ID-410B 1L0532Y24I0TD001 264-7SYGD/S530-E2 HLMP-1301-G00FG HLMP1385 LTL-10224W LTL-1224A LTL-1234A LTL-2251AT LTL-403HR LTL-4222 LU7-E-B 4380H1 HLMP-3962-F0002 HLMP-GG15-R0000 L53SRC/E-Z L-7679C1ZGC 4302T1-5V 4306D23 4363D1/5 WP1503SRC/J4 WP153YDT WP1543SGC WP1543SRC/D WP1543SURC WP53MGD WP7113MD WP7113MBD WP7113MGC WP7143SEC/H Z-221A