


Dialight

564 Series

3mm LED CBI®

Circuit Board Indicator

TRI-LEVEL



FEATURES / BENEFITS


- ▲ Multiple CBIs form horizontal LED arrays on 4.45 mm (0.175") center lines.
- ▲ High Contrast, UL 94 V-0 rated, black housing
- ▲ Housing stand-offs facilitate PCB cleaning
- ▲ Solderability per MIL-STD-202F, method 208F
- ▲ LEDs are safe for direct viewing per IEC 825-1, EN 60825-1

PART NUMBER


COLOR COMBO *

HIGH EFFICIENCY - LED TYPE 1	
564-0140-111	RED/RED/RED
564-0140-132	RED/YELLOW/GREEN
564-0140-222	GREEN/GREEN/GREEN
564-0140-777	ORANGE/ORANGE/ORANGE
LOW CURRENT - LED TYPE 2	
564-0240-111	RED/RED/RED
564-0240-132	RED/YELLOW/GREEN
564-0240-222	GREEN/GREEN/GREEN
INTEGRAL RESISTOR, 5 VOLTS - LED TYPE 2	
564-0340-111	RED/RED/RED
564-0340-132	RED/YELLOW/GREEN
564-0340-222	GREEN/GREEN/GREEN
BI-COLOR - LED TYPE 7	
564-0740-111	RED/GREEN-RED/GREEN-
	RED/GREEN
564-0740-444	YELLOW/GREEN-YELLOW/GREEN-
	YELLOW/GREEN


* Top-Middle-Bottom LED



PART NUMBER ORDERING CODE



ATTENTION:
OBSERVE
PRECAUTIONS
FOR HANDLING
ELECTROSTATIC
DEVICES



Contact factory for information on custom color combinations.

Dialight Corporation

1501 Route 34 South • Farmingdale, NJ 07727 USA

Tel: (1) 732-919-3119 • Fax: (1) 732-751-5778 • www.dialight.com





**3mm LED CBI® Circuit Board Indicator
Tri-Level**

OPERATING CHARACTERISTICS (TA= 25°C)

HIGH EFFICIENCY - LED TYPE 1

Part Number	Color	Peak Wavelength (nm)	Iv mcd	V _F volts	Test Current (mA)	Viewing Angle 2θ 1/2
564-0140-xxx	Red	635	10.0	2.0*	10	60°
	Green	565	12.6	2.1*	10	60°
	Yellow	585	10.0	2.1*	10	60°
	Orange	600	7.0	2.2	10	60°

*I_F = 20mA

LOW CURRENT - LED TYPE 2

Part Number	Color	Peak Wavelength (nm)	Iv mcd	V _F volts	Test Current (mA)	Viewing Angle 2θ 1/2
564-0240-xxx	Red	635	1.6	1.7	2	60°
	Green	565	1.6	1.9	2	60°
	Yellow	585	1.6	1.8	2	60°

INTEGRAL RESISTOR, 5 VOLTS - LED TYPE 3

Part Number	Color	Peak Wavelength (nm)	Iv mcd	Test Voltage	Test Current (mA)	Viewing Angle 2θ 1/2
564-0340-xxx	Red	635	29	5	10	60°
	Green	565	19	5	10	60°
	Yellow	585	12.6	5	10	60°

BI-COLOR - LED TYPE 7

Part Number	Color	Peak Wavelength (nm)	Iv mcd	V _F volts	Test Current (mA)	Viewing Angle 2θ 1/2
564-0740-111	Red/Green	635/565	4.7/10.0	2.0/2.1*	10	60°
564-0740-444	Yellow/Green	585/565	4.3/6.3	2.1*	10	80°

*I_F = 20mA

DIALIGHT RESERVES THE RIGHT TO MAKE CHANGES AT ANY TIME IN ORDER TO SUPPLY THE BEST PRODUCT POSSIBLE.

Dialight Corporation

1501 Route 34 South • Farmingdale, NJ 07727 USA

Tel: (1) 732-919-3119 • Fax: (1) 732-751-5778 • www.dialight.com



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [LED Circuit Board Indicators](#) category:

Click to view products by [Dialight](#) manufacturer:

Other Similar products are found below :

[568-0701-841F](#) [LTL-4221NH129](#) [LTL-42DGNMHDP1](#) [HLMP1521101](#) [HLMP1523802F](#) [HLMP1700101F](#) [HLMP1700104F](#) [BHA-1564-G](#)
[SMF-HM1530YD-305](#) [SSF-LXH409SYSUGW](#) [AM2520EHSGD](#) [HLMP1301104F](#) [HLMP1385101F](#) [HLMP1421101](#) [HLMP1503103F](#)
[HLMP1503104F](#) [HLMP1700102F](#) [HLMP1700106F](#) [HLMP1700107F](#) [HLMP1790101F](#) [HLMP1790103F](#) [LTL-4211NHBP](#) [5390H3](#) [551-](#)
[2802F](#) [552-0794-810F](#) [553-0222-812F](#) [HT3-BC-T](#) [564-0700-831F](#) [WP59BLGEW](#) [103-3101-1231-403](#) [5502407811F](#) [550-3007-810F](#) [551-](#)
[3307MF](#) [552080-1](#) [573-2399-100F](#) [592-2020-302F](#) [5932-927-2701-3F](#) [SMF-HM1530SRD-509](#) [SSF-LXH100MID](#) [SSF-LXH2103SRSDRP](#)
[SSF-LXH555USBW](#) [WP937SB/4YGW](#) [WP937EB2EGW](#) [551-0312-802F](#) [553-0110-802F](#) [561-5501-050F](#) [6202T3-5VLC](#) [LTL-307G08A-D](#)
[CMD57164](#) [568-2231-313F](#)