



linear dimension (Tolerances Standard GB/T 14486-2008)

tolerance	variable range
±0.1	6 to 10
±0.14	10 to 18
±0.19	18 to 30
±0.25	30 to 50
±0.32	50 to 80
±0.43	80 to 120
±0.57	120 to 160
±0.72	160 to 200
±0.88	200 to 250
±1.05	250 to over
±1.25	all
0.5	5 to 5
0.025	5 to 30
0.06	30 to 120
0.12	120 to over
0.4	120 to over

单位 / UNITS: mm 尺寸 / SIZE: A4 比例 / SCALE: 5:2

名称 / TITLE: DB129V-5.0/5.08-XXP

第三视角 / THIRD ANGLE PROJECTION

Cixi Dibo Electronics Co., LTD

- 电气性能 / Electrical: 参考标准 / Standard: UL, 300V, IEC; 额定电压 / Rated voltage: 300V; 额定电流 / Rated current: 16A, 24A; 接触电阻 / Contact resistance: 20mΩ; 绝缘电阻 / Insulation resistance: 500MΩ / DC500V; 使用线径 / Wire range: 26~12AWG 2.5mm²; 耐电压 / Wrth standing voltage: AC 2000V/1 Min
- 机械性能 / Mechanical: 扭矩 / Torque: 0.5Nm(4.5lb.in); 剥线长度 / Steip Length: 6-7mm; 温度范围 / Temp. Range: -40°C~+105°C; 瞬时温度 / MAX Soldering: +250°C, for 5 Sec; 尺寸 / Dimensions: 间距 / Pitch: 5.0mm, 5.08mm; 极数 / Poles: 2~24p
- 材质及电镀 / Material: 塑件 / Housing: PA66, UL94V-0; 螺丝 / Screws: M3.0, Steel Zn plated; 焊脚 / Pin header: Brass, Tin plated; 方块 / Cage: Brass, Ni plated

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Terminal Blocks](#) category:

Click to view products by [DIBO](#) manufacturer:

Other Similar products are found below :

[00175550202](#) [MBE-1512](#) [MBE-1520](#) [MBE-154](#) [MBE-156](#) [MBES-1510](#) [MBES-153](#) [MBES-156](#) [MH-2512](#) [MHE-132](#) [MHE-133](#) [MHE-163](#)
[MI-254 \(35\)](#) [MI-272](#) [8739](#) [880507](#) [880508](#) [MPT-275](#) [1546551-6](#) [ELM023100](#) [ELM10110G](#) [ELVD12100](#) [BA311TU](#) [BA411SU](#) [MV-152](#)
[MV-253/NCNOC](#) [MV-254-D](#) [MV-255](#) [MV-462](#) [MV-472](#) [MV-493](#) [MVE-252](#) [MVE-253](#) [MVE-258](#) [MVE-273](#) [MVEB-153](#) [1700096](#)
[1702246](#) [1705142](#) [1712417](#) [1713020](#) [1713088](#) [1776118-2](#) [1790852](#) [1-796689-8](#) [1-796692-6](#) [1800001](#) [1800114](#) [1823215](#) [1838462](#)